# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




# Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




	REVISIONS			
This drawing and the information set forth hereon are the property of Tyco		DESCRIPTION	APPROVAL	DATE
Electronics Corporation and are to be held in trust and confidence. Publication, duplication, disclosure or use for any purpose not expressly authorized in writing by Tyco Electronics Corporation is prohibited.	А	REVISED PER ECN T-18756	ZET	23NOV1993
	В	REVISED PER ECO 09-007936	E.CHEN	30MAR2009
	B1	CORRECTED TYPO ON SLEEVE PER ECO-10-010916	E.CHEN	24MAY2010




# OUTER SEALING SLEEVE



# FLEXIBLE SOLDERSHIELD



# INNER SEALING SLEEVE



# **INSULATION SLEEVE (2/Kit)**

CRIMP (2/Kit)

Unless otherwise s dimensions are in (Inches dimension	millimeters.	REDRAWN E.CHEN DRAWN	DATE 26MAR2009 DATE	<b>E</b> Tyco Electronics		Raychem Databus Products 300 Constitution Drive Menlo Park, CA. 94025, U.S.A.	
parenthesis) TOLERANCES 0.001 ±N/A 0.01 ±N/A 0.1 ±N/A	ANGLES 1° ±N/A	ZET MATERIAL	07JUL1992	TITLE: Flexible Splice Kit			
RPN 449453 CAD FILE D-150-070		FINISH		SIZE A DO NOT	CAGE CODE 06090 SCALE THIS DRAWING	DWG. NO. D-150-0708-5 SHEET 1 OF 2	REV. B1

# CUSTOMER DRAWING

© 2006-2010 Tyco Electronics Corporation. All rights reserved.

If this document is printed it becomes uncontrolled. Check for the latest revision.

NOTES:

- 1.0 <u>MATERIALS</u>
- 1.1 OUTER SEALING SLEEVE: High temperature fluid stabilized cross-linked elastomer to Raychem specification RK-6008, black. Sealing inserts: Modified stabilized elastomer fluoropolymer thermoplastic.
- FLEXIBLE SOLDERSHIELD: Double shielded, tin plated copper wire braid, pre-tinned with Sn96 per IPC J-STD-006 solder. Pre-installed terminators: Insulation sleeves with Sn96 solder per IPC J-STD-006 preforms.
- 1.3 INNER SEALING SLEEVE: High temperature fluid stabilized cross linked elastomer to Raychem specification RK-6008, sealing inserts: modified stabilized elastomer fluoropolymer thermoplastic, black.
- 1.4 INSULATION SLEEVE: Heat-shrinkable, transparent blue, radiation cross-linked modified polyvinylidene fluoride.
- 1.5 CRIMP FERRULE: Copper Alloy 102 per ASTM B75. Tin plated per MIL-T-10727 Type 1. Red stripe code.

## 2.0 <u>APPLICATION</u>

- 2.1 This flexible splice kit is designed to facilitate the assembly or maintenance of pre-cabled digital harness components for MIL-STD-1553B networks
- 2.2 To be used where continuous flexing is not a functional requirement.
- 2.3 Cables to be accommodated: 8421526-AO-01, 8421526-BO-01, 8421526-CO-01, 8421527-DO-01, and 8421528-EO-01.
- 2.4 Minimum bend radius, static 80mm. Dynamic: not recommended.
- 2.5 Installation procedure and tooling: Raychem RPIP-600-12.
- 2.6 For applications other than above, consult Raychem technical services.

### 3.0 <u>TEMPERATURE RATING</u>

3.1 Operating temperature: -65°C to +150°C, brief excursions to +200°C permissible without degradation.

## 4.0 PERFORMANCE SPECIFICATIONS

4.1 Designed to meet the performance requirements of U.S. Air Force 8340708.

#### CUSTOMER DRAWING

REDRAWN BY E.CHENCAGE CODE 06090REPLACES: BECC	10.010016 B1 D 150.0708 5	SCALE SIZI None	E: SHEET: A 2 of 2
---	---------------------------	--------------------	-----------------------

© 2006-2010 Tyco Electronics Corporation. All rights reserved.

If this document is printed it becomes uncontrolled. Check for the latest revision.