



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





TEL: 973-328-3200 FAX: 973-328-3130

[Home](#) > [Tubing](#) > [Non-Shrinkable Tubing](#) > #D200 DAFLEX Silicone Rubber Coated Fiberglass Sleeving MIL-I-3190/6

#D200 DAFLEX Silicone Rubber Coated Fiberglass Sleeving MIL-I-3190/6

Description: Braided fiberglass sleeving with a uniform coating of silicone rubber. Cuts cleanly and will not fray. The tubing remains flexible from -55°C to +200°C. Can be "pushed-back" easily; has high cut through resistance, and is unaffected by corona, ozone, radiation, weathering and fungus, with excellent abrasion, chemical and moisture resistance, self-extinguishes flame. UL Rated: 600V.

This series is RoHS compliant.

DAFLEX Cat. No.	Size	MIL-I-3190 Size	Inside Diameter (IN.)			Stock Spool or Coil
			Min.	Nom.	Max.	
D200-24	24	01	0.02	0.022	0.027	100', 500', 1000'
D200-22	22	02	0.025	0.027	0.032	100', 500', 1000'
D200-20	20	03	0.032	0.034	0.039	100', 500', 1000'
D200-18	18	04	0.040	0.042	0.049	100', 500', 1000'
D200-16	16	06	0.051	0.053	0.061	100', 500', 1000'
D200-15	15	07	0.057	0.059	0.067	100', 500', 1000'
D200-14	14	08	0.064	0.066	0.074	100', 500'
D200-13	13	09	0.072	0.076	0.082	100', 500'
D200-12	12	10	0.081	0.085	0.091	100', 500'
D200-11	11	11	0.091	0.095	0.101	100', 500'
D200-10	10	12	0.102	0.106	0.112	100', 500'
D200-9	9	13	0.114	0.118	0.124	100', 500'
D200-8	8	14	0.129	0.133	0.141	100', 500'
D200-7	7	15	0.144	0.148	0.158	100', 500'
D200-6	6	16	0.162	0.166	0.178	100'
D200-5	5	17	0.182	0.186	0.198	100'
D200-4	4	18	0.204	0.208	0.224	100'
D200-3	3	19	0.229	0.234	0.249	100'
D200-2	2	20	0.258	0.263	0.278	100'
D200-1	1	21	0.289	0.294	0.311	100'
D200-0	0	22	0.325	0.330	0.347	100'
D200-3/8	3/8"	23	0.375	0.387	0.399	100'
D200-7/16	7/16"	24	0.438	0.450	0.462	100'
D200-1/2	1/2"	25	0.500	0.512	0.524	100'
D200-5/8	5/8"	26	0.625	0.640	0.655	100'
D200-3/4	3/4"	27	0.750	0.768	0.786	100'
D200-7/8	7/8"	28	0.875	0.893	0.911	100'
D200-1"	1"	29	1.000	1.006	1.036	100'

Stock Color: White. Additional colors and grades available to order.

Specifications: NEMA Grade A, (7000V) Class "R", VS-1, ASTM-D372, UL Standard 1441, MIL-I-3190/6 Grade A.