



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us



Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



The reproduction, distribution or use of this document in any form or by any means, electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, is prohibited without the express written permission of the copyright owner.



Hinweis / Remark:

NC und NO dürfen bei gleichzeitigem Betrieb nur an gleichem Potential betrieben werden.
Die geforderten Kriech- und Luftstrecken werden bei aufgesteckten Flachsteckhülsen unterschritten, deren Einhaltung muß durch die Art des Einbaues sichergestellt werden oder der Anschluß darf nur mit geeigneten isolierten Flachsteckhülsen erfolgen.
NC and NO shall only be used at the same electrically potential.

The requirements of the precrepage distances or clearances with mounted female tabs are not fulfilled, they have to be met by use of suitable insulated female tabs or by the way of building-in.

Weitere Angaben siehe technische Spezifikation TS-D4-00001.

Bei Abweichungen gelten die Zeichnungsangaben.

bei Abweichungen gelten die Zeichnungsangaben.
Further details please refer to technical specification TS-D4-000001.
In case there are any deviations, the details of the drawing have priority.

51	17.12.12	HZ	176889	
50	16.08.12	HZ	176234	
Index Rev.	Date	Name	Änderung / Modification AM-Nr. / Document-No.	

Werkstoffe / Materials:

Gehäuse, Deckel: PET, UL 94 V-0
Case, Cover

Betätiger : POM, UL 94 HB
Button

Anschluß COM : CuZn37, gal. Ag/silver plated
Terminal

Anschluß NC. NO: CuZn37
Terminal

Kontakte
Contacts

Zusatzbetätiger: DC03, gal. Ni/nickel plated
Aux. Actuator

Allgemeintoleranzen nach / General tolerances according to DIN ISO 2768-m

Winkeltoleranzen / Angle tolerances: $\pm 2^\circ$ 

ZF Friedrichshafen AG
Electronic Systems
DE-91275 Auerbach/Dnfr

CAP-Ablage / CAP-file: /ems/d4/sts/d4333-r11d

D433 - R1LD