# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



#### **Spec Sheet**

# FBAR/SAW Devices (SAW Duplexers) D5DA942M5K2G6



#### Features

- Item Summary
  - SAW, Duplexer, 1.8x1.4x0.5mm
  - Band 8
- Lifecycle Stage
- Mass Production
- Standard packaging quantity (minimum)
  - Taping Embossed 3000 , 15000pcs

#### Products characteristics table

System	W-CDMA / LTE
Туре	SAW
Function	Duplexer
band	Band 8
Insertion Loss (typ) (Tx-ANT/ANT-Rx)	1.7/1.8 dB
Isolation (typ)	58/59 dB
Operating Temp. Range	-20 to +85 °C
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

#### External Dimensions

Dimension L	1.8 + 0/- 0.20 mm
Dimension W	1.4 + 0/- 0.20 mm
Dimension T	Max 0.5 mm

The data is reference only. Electrical characteristics vary depending on environment or measurement condition. TAIYO YUDEN reserves the right to make change to the Date at any time without notice. Before making final selection, please check product specification.





Customer Name	Standard	TAIYO YUDEN Mobile Technology Co., Ltd.		
System	Band 8 Duplexer	DATE	Mar. 6, 2015	
Part Number	D5DA942M5K2G6	Version 2.1bbD	Final	

#### Table 1. Electrical Specification

	11		Condition		Specificatio	on		
	ltem		(MHz)	Min	Тур	Max	Unit	Remarks
Tx	Insertion loss		882.4~912.6	-	1.7	2.5 <mark>(*2)</mark>	dB (*1)	
to			880.24~914.76	-	2.1	3.4	dB (*1)	
ANT			880~915	-	1.3	2.9	dB	
	Input Pov	wer	882.4~912.6		, Ta=+50∘0 DMA modu		-	
		Тх	880~915	-	1.6	2.2		
	VSWR	Ant	880~915	-	1.5	2.2	-	
	Absolute		927.4~957.6	48(*2)	60	-	dB	
	Attenuati	on	1573.3~1605.9	40	46	-	dB	
			1760~1830	40	47	-	dB	
			2640~2745	28	35	-	dB	
ANT	ANT to		927.4~957.6	-	1.8	2.5 <mark>(*2)</mark>	dB (*1)	
to			925~960	-	2.0	3.1	dB (*1)	
Rx	Ripple		925~960	-	0.9	2.3	dB	
	VSWR An		925~960	-	1.8	2.3	-	
	VOVIN	Rx	925~960	-	1.7	2.2	-	
	Absolute		882.4~912.6	50 <mark>(*2)</mark>	57	-	dB	
	Attenuati	on	2400~2500	40	51	-	dB	
Tx to Rx	Isolation		882.4~912.6	55 <mark>(*2)</mark>	58	-	dB	
				55 <mark>(*2)</mark>	59	-	dB	0 to +85∘C
			927.4~957.6	53 <mark>(*2)</mark>	-	-	dB	-10 to 0ºC
				50 <mark>(*2)</mark>	-	-	dB	-20 to -10ºC
Terminatin	ng Impedar	ice	Tx port		50 // 33nH	1	Ohm	Single-ended
			Rx port		50		Ohm	Single-ended
	Ant port		50 // 8.2nH		Ohm	Single-ended		
Operating	Operating Temperature			-20 to +85	5	٥C		
Device siz	Device size (L max. x W max. x H max.)		1	.8 x 1.4 x (	0.5	mm		

(\*1) Specification of insertion loss excludes loss that comes from the test board.


(\*2) Integrated over +/-1.92MHz around the WCDMA channel center frequency





Customer NameStandardTAIYO YUDEN Mobile Technology Co., Ltd.SystemBand 8 DuplexerDATEMar. 6, 2015Part NumberD5DA942M5K2G6Version 2.1bbDFinal

#### **Dimensions**



Unit: mm

#### **Pin Configuration**

Pin No.	Pin name	Description
1	Rx	Receiver Pin
2	GND	Ground Pin
3	Тх	Transmitter Pin
4	GND	Ground Pin
5	GND	Ground Pin
6	ANT	Antenna Pin
7	GND	Ground Pin
8	GND	Ground Pin


#### Figure 1. Dimensions and Pin assignment






Customer NameStandardTAIYO YUDEN Mobile Technology Co.,Ltd.SystemBand 8 DuplexerDATEMar. 6, 2015Part NumberD5DA942M5K2G6Version 2.1bbDFinal

#### **Evaluation Circuit**





#### **Recommended foot print pattern**





Figure 3. Recommended foot print pattern






Customer NameStandardTAIYO YUDEN Mobile Technology Co.,Ltd.SystemBand 8 DuplexerDATEMar. 6, 2015Part NumberD5DA942M5K2G6Version 2.1bbDFinal

#### Tx to Ant







These data exclude loss that comes from the test board.







Pb-free \* Pb Free Part

Customer Name	Standard	TAIYO YUDEN Mobile	e Technology Co.,Ltd.
System	Band 8 Duplexer	DATE	Mar. 6, 2015
Part Number	D5DA942M5K2G6	Version 2.1bbD	Final

### Tx to Ant, Ant to Rx



Tx to Rx Isolation



These data exclude loss that comes from the test board.





Customer Name	Standard	TAIYO YUDEN Mobile	e Technology Co., Ltd.
System	Band 8 Duplexer	DATE	Mar. 6, 2015
Part Number	D5DA942M5K2G6	Version 2.1bbD	Final






Figure 4-3. Electrical Characteristics





Customer Name	Standard	TAIYO YUDEN Mobile	e Technology Co., Ltd.
System	Band 8 Duplexer	DATE	Mar. 6, 2015
Part Number	D5DA942M5K2G6	Version 2.1bbD	Final

### **Rx Port**




Figure 4-4. Electrical Characteristics





Customer Name	Standard	TAIYO YUDEN Mobile	e Technology Co., Ltd.
System	Band 8 Duplexer	DATE	Mar. 6, 2015
Part Number	D5DA942M5K2G6	Version 2.1bbD	Final

### Ant Port





Figure 4-5. Electrical Characteristics





Customer NameStandardTAIYO YUDEN Mobile Technology Co.,Ltd.SystemBand 8 DuplexerDATEMar. 6, 2015Part NumberD5DA942M5K2G6Version 2.1bbDFinal

### Tx to Ant (Wide span)








Figure 4-6. Electrical Characteristics





Customer Name	Standard	TAIYO YUDEN Mobile Technology Co., Ltd.		
System	Band 8 Duplexer	DATE	Mar. 6, 2015	
Part Number	D5DA942M5K2G6	Version 2.1bbD	Final	

#### **Ordering Code**

Ordering Code	Packing	Reel size	Status
D5DA942M5K2G6 <mark>-Z</mark>	Tape & Reel	3,000 pcs.	MP
D5DA942M5K2G6- <mark>Z</mark> A	Tape & Reel	less than 3,000 pcs.	MP
D5DA942M5K2G6 <b>-Y</b>	Tape & Reel	15,000 pcs.	MP
D5DA942M5K2G6- <mark>Y</mark> A	Tape & Reel	less than 15,000 pcs.	MP
D5DA942M5K2G6-Q	Bulk	few pcs.	MP

\*Minimum order quantity (MOQ) is assigned for each inquiry, Please contact to Sales Representatives. \*MP: Mass production

#### **Notice**

All of the contents specified herein are subject to change without notice due to technical improvements, etc.

Please contact Taiyo Yuden Co., Ltd. for further details of product specifications.

Please conduct validation and verification of products in actual condition of mounting and operating environment before commercial shipment of the equipment.

This product is for general electronics equipment such as Audio-Visual equipment, household electronics, office supplies, information services and telecommunications; therefore, in case this product is used for any medical equipment, space equipment, nuclear equipment or disaster prevention equipment, please contact Taiyo Yuden in advance.

In case this product is used for general electronics equipment or circuits which require high safety and high reliability, thoroughly evaluate on safety and add a protection circuit if necessary.