

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








DA1206E300R-10

UNCONTROLLED DOCUMENT


PHYSICAL DIMENSIONS:


A 3.20 [.126] \pm 0.20 [.008] B 1.60 [.063] ± 0.20 [.008] C 0.80 [.031] ± 0.20 [.008] D 0.40 [.016] ± 0.15 [.006] D1 0.30 [.012] ± 0.20 [.008]

E 0.80 [.031] ± 0.10 [.004]




Z vs. FREQUENCY IMPEDANCE UNDER DC BIAS






HP 16092A Test Fixture. TEST REF. 3124





LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.762 (0.030) to this dimension)


ELECTRICAL CHARACTERISTICS:									
Z @ 100N (<mark>Ω</mark>)		DCR $\left(\begin{array}{c}\Omega\end{array}\right)$	Rated Current						
Nominal	30								
Minimum	23								
Maximum	38	0.3	500 mA						

LINE TO LINE INSULATION RESISTANCE >100 M Ω AT 75 VOLTS.

NOTES: UNLESS OTHERWISE SPECIFIED

- 1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 3000 PCS/REEL.
- 2. TERMINATION FINISH IS 100% TIN.
- 3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
- 4. OPERATING TEMPERATURE TEMP: -40°C~+125°C (INCLUDING SELF-HEATING)

RECOMMENDED SOLDERING CONDITIONS



DIMENSIONS ARE IN mm [INCHES].			This print is the property of Laird					
				Tech, and is loaned in confidence subject to return upon request and	▗▎█▗▄▐▗▗▗▛▘			
				with the understanding that no		2	ırı	
				copies shall be made without the	Laird			
				written consent of Laird Tech. All rights to design or invention are	_			
D	OPERATING TEMPERATURE UPDATE LAIRD LOGO AND REFLOW CURVE	08/05/13	QU	reserved.				
	OPDATE LAIRD LOGO AND REFLOW CORVE				REV	PART TY	PE:	DRAWN BY:
С	UPDATE COMPANY LOGO	05/22/09	JRK	DA1206E300R-10	D	L co-	FIRE	тмв
В	D1 dim chgd from 0.008 ±0.004 to 0.012 ±	10/31/07	JRK	DATIZOOLOGOR TO			TINE	111110
لــــّــا	0.008.ADD ROHS, UPDATE COMPANY LOGO			DATE: 03/30/04 SCA	LE: N	TS	SHEET:	
Α	ORIGINAL DRAFT	03/30/04	ТМВ	CAD #				
REV	DESCRIPTION	DATE	INT		- •	-	2	of 2