



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Timers

Delay on Operate

Types DAA51, DAA71

CARLO GAVAZZI



DAA51



DAA71

- Time range 0.1 s to 100 h
- Knob selection of time range
- Knob adjustable time setting
- Automatic start
- Repeatability: $\leq 0.2\%$
- Output: 5 A SPDT or 5 A DPDT relays
- For mounting on DIN-rail in accordance with DIN/EN 50 022
- 17.5 mm (DAA51C) or 35.5 mm (DAA71D) DIN-rail housing (DIN 43880)
- Combined AC and DC power supply
- LED indication for relay status and power supply ON

Product Description

Multi-voltage delay on operate timer with 7 selectable time ranges within 0.1 s and 100 h. For mounting on DIN-rail

Housing 17.5 mm wide for SPDT version and 35.5 mm for DPDT version, suitable both for back and front panel mounting.

Ordering Key

DAA 51 C M24

Housing _____
 Function _____
 Type _____
 Item number _____
 Output _____
 Power supply _____

Type Selection

Mounting	Output	Housing	Supply: 12 to 240 VAC/DC	Supply: 24 VDC and 24 to 240 VAC
DIN-rail	SPDT	Mini-D		DAA 51 C M24
DIN-rail	DPDT	Mini-D	DAA 71 D W24	DAA 71 D M24

Time Specifications

Time ranges Knob selectable	0.1 to 1 s	Repeatability $\leq 0.2\%$	
	1 to 10 s		
	6 to 60 s		
	60 to 600 s		
	0.1 to 1 h		
Setting accuracy	1 to 10 h	Time variation Within rated power supply $\leq 0.05\%/V$ Within ambient temperature $\leq 0.2\%/^{\circ}C$	
	10 to 100 h		
	$\leq 5\%$		
	Reset		≥ 200 ms
	Power supply interruption		

Supply Specifications

Power supply Rated operational voltage through terminals:	Overvoltage cat. II (IEC 60664, IEC 60038)
(DAA51C) A1, A2 M24	24 VDC $\pm 15\%$ and 24 to 240 VAC +10% -15%, 45 to 65 Hz
(DAA71D) A1, A2 M24	24 to 240 VAC +10% -15%, 45 to 65 Hz
W24	12 to 240 VDC +10% -15% and 12 to 240 VAC +10% -15%, 45 to 65 Hz
Voltage interruption	≤ 10 ms
Rated operational power	
(DAA51C) AC supply	4 VA
DC supply	1.5 W
(DAA71D) AC supply	5.5 VA
DC supply	2 W

Output Specifications

Output	SPDT or DPDT relays
Rated insulation voltage	250 VAC (rms)
Contact Ratings (AgSnO₂)	μ
DAA51 (SPDT):	
Resistive loads	AC 1 5 A @ 250 VAC DC 12 5 A @ 24 VDC
Small inductive loads	AC 15 2.5 A @ 250 VAC DC 13 2.5 A @ 24 VDC
DAA71 (DPDT)	
Resistive loads	AC 1 5 A @ 250 VAC
Small inductive loads	AC 15 3 A @ 250 VAC DC 13 3 A @ 24 VDC
Mechanical life	$\geq 30 \times 10^6$ operations
Electrical life	$\geq 10^5$ operations (at 5 A, 250 V, $\cos \varphi = 1$)
Operating frequency	< 7200 operations/h
Dielectric strength	
Dielectric voltage	2 kVAC (rms)
Rated impulse withstand voltage	2.5 kV (1.2/50 μ s)

General Specifications

Power ON delay	≤ 100 ms	
Indication for	LED, green	
Power supply ON	LED, yellow	
Output relays ON	(flashing when timing)	
Environment	(EN 60529)	
Degree of protection	IP 20	
Pollution degree	2 (IEC 60664)	
Operating temperature	-20° to +60°C, R.H. < 95%	
Storage temperature	-30° to +80°C, R.H. < 95%	
Housing		
Dimesions	(DAA51C)	17.5 x 81 x 67.2 mm
	(DAA71D)	35.5 x 81 x 67.2 mm
Material	PA66	
Weight	75 g	
Screw terminals		
Tightening torque	Max. 0.5 Nm according to IEC EN 60947	
Approvals	UL, CSA RINA (DAA51 only)	
CE Marking	Yes	
EMC	Electromagnetic Compatibillity	
Immunity	According to EN 61000-6-2	
Emission	According to EN 61000-6-3	

Mode of Operation

The yellow LED, flashing when timing, is ON as soon as the relay turns ON.

The set delay period begins as soon as the power supply is connected. At the end of the set delay the relay operates and does not release until the power supply is interrupted for at least 200

ms. If the power supply is interrupted for at least 200 ms before the relay operates the time is set to zero and the circuit is ready for a new time period.

Time Setting


Centre knob:

Time setting on relative scale: From 1 to 10 with respect to the chosen range.


Lower knob:

Setting of time range

Operating Diagram



Wiring Diagram



Dimensions

