



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Datasheet for part number DAUE15SA197F0

|                                           |                                                             |
|-------------------------------------------|-------------------------------------------------------------|
| Our Catalog Part Number: DAUE-15S-A197-F0 |                                                             |
| Brand: Cannon                             | Product Category: D Sub   Product Line: D Sub   Series: D*U |

| Product Datasheet               |                                                    |
|---------------------------------|----------------------------------------------------|
| General                         | Low Cost Crimp Connector                           |
| Wire Gauge Range AWG            | AWG 18-30                                          |
| Mating Cycles                   | 50, 200, 500                                       |
| Dielectric Withstanding Voltage | 1000 VAC at sea level                              |
| Current Rating                  | 5 A max                                            |
| Contact Resistance              | 15 milli Ohm max                                   |
| Operating Temperature           | -55°/+125°                                         |
| Salt Spray Test                 | 20 hours                                           |
| Shell Material                  | steel                                              |
| Shell Finish                    | tin/nickel                                         |
| Insulator Material              | glass filled Thermoplastic, type PCT UL 94V-0      |
| Insulator Color                 | black                                              |
| Contact Arrangement             | 15 contacts size 20                                |
| Gender                          | Socket                                             |
| Contacts                        | delivery without contacts, please order separately |
| Contact Type                    | stamped                                            |
| Contact Material                | copper alloy                                       |
| Contact Finish                  | gold over nickel                                   |
| Contact Termination             | Crimp                                              |
| Mounting Methode                | 4-40 Clinchnut                                     |