



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



DC-11201-1

2 Port - USB 2.0-KVM



Features

- Controls 2 PCs with one PS/2 or USB keyboard, one PS/2 or USB mouse, and one monitor.
- Supports Windows, Linux, Mac OS9/OSX, Sun Micro Solaris 8
- Supports USB to PS/2 keyboard and mouse conversion; eliminates the need for one set of keyboard and mouse cables.
- Supports 3 USB 2.0 downstream ports (perfect for sharing USB scanners, USB printers, and USB CD-RW, etc.)
- Supports 3 types of switching: hardware push button, hot keys on PS/2 keyboard, and On-Screen-Display (OSD) utility software (for Windows).
- OSD utility indicates:
 - 1st Power status of connected computer(s).
 - 2nd Active host computer.
- Supports VGA resolutions up to 2048x1536.
- Plug and Play. No software driver is needed for PS/2 mouse and keyboard operation.
- Incl. two 1,8 m cable sets HDB15/M, 1xUSB-A/M ⇔ HDB15/F, 1xUSB-B/M

System requirements

- **Computer:** USB port, VGA port
- **Operating System:** Windows 98/98SE/2000/ME/XP, Mac OS9/OSX, Linux Kernel 2.3 or Later, Solaris 8.
- **VGA Cable:** 1 VGA female-to-male cable per computer
- **USB Cable:** 1 USB cable with one Type-A end and one Type-B end per computer

Connectors

- 1 Mini-DIN for PS/2 keyboard
- 1 Mini-DIN for PS/2 mouse
- 3 USB 2.0 type A downstream connectors
- 2 USB 2.0 type B upstream connectors
- 2 VGA input connectors (HDB15 Female), and one VGA output connector (HDB15 Female).

Specifications

Model	DC-11201-1
Complies USB revision	USB 1.0, 1.1, 2.0
Working PC status LED	2
USB 2.0 upstream port	2
VGA IN port	2
VGA OUT port	1
USB 2.0 downstream port	3
USB over current LED indicator	3
PS/2 keyboard port	1
PS/2 mouse port	1
Video resolution	2048 X 1536.
Hardware supported	PC/Mac/Sun Micro
OS Supported	Windows 98/98SE/ME/2000/XP, Mac OS9/OSX Linux Kernel 2.3/above Solaris 8/above
Active PC selection	By push button By hotkey (only in PS/2 keyboard) By OSD utility(Windows)

Package Contents

- 2 port USB 2.0 KVM Switch
- CD with users manual, On-Screen-Display(OSD) utility