



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



2 / 4 Port - USB-PS/2 Combo KVMs



Features

1. Console your Keyboard/Mouse via either way of PS/2 and/or USB arbitrarily.
2. Complex connections with PCs via either way of PS/2 and/or USB arbitrarily.
3. Controls 2 / 4 computers from a single console (Keyboard/Mouse) over PS/2 and/or USB connections.
4. Supports Windows, Linux, Mac OS9/OSX, Sun Microsystems.
5. Emulates a keyboard on each PC to allow your computers to boot normally - without a keyboard error.
6. Supports hot-swap. All devices connected to the KVM can be added or removed at any time, without shutting the unit down.
7. Supports 2 types of switching:
 - (1) Hardware Push Button
 - (2) Hot-Keys on PS/2 and/or USB of keyboard arbitrarily.
8. Supports Auto-Scan function to alternate video between computers in preset intervals.
9. Supports LED display for PC status monitoring.
10. Supports VGA resolutions up to 2048 x 1536 @ 85HZ.
11. Supports Beeper during switching enabled.
12. Self powered through PS/2 and/or USB connection.
13. Fully compliant with the USB 1.1/ 2.0 specification.
14. Audio support IN / OUT (only audio version)
15. Incl. two 1,8 m KVM cable sets (HDDDB15/M ⇔ HDDDB15/M, 2xMiniDIN6/M, 1xUSB-A/M; audio version additional with two cable 2x3,5mm stereo/M ⇔ 2x3,5mm stereo/M)

System Requirements

Console

- A VGA, SVGA, Multisync monitor capable of the highest resolution.
- PS/2 and/or USB Keyboard/Mouse

Computer or Server

The following equipment must be equipped with each computer or server.

- A VGA, SVGA or Multisync card.
- Type A USB port and/or PS/2 6 pin mini-DIN for Keyboard and Mouse.

Specification

Number Of Computers Controlled	2 / 4	
Selection Method	Push Button and Hot-Key (PS/2 and/or USB Keyboard)	
LEDs	Red for PC Selection Green for PC On-Line ready	
PC Connectors	Video	2 / 4 x HDB -15 female (USB & PS/2 signal combined)
	Speaker	2 / 4 audio female jacket (only audio version)
	Microphone	2 / 4 audio female jacket (only audio version)
Console Ports	Keyboard	1 x 6 pin PS/2 mini-DIN female 1 x USB A type female (only USB –PS/2 version)
	Mouse	1 x 6 pin PS/2 mini-DIN female 1 x USB A type female (only USB –PS/2 version)
	Video	1 x HDB -15 female
	Speaker	1 x audio female jacket (only audio version)
	Microphone	1 x audio female jacket (only audio version)
	Auto-Scan Interval	From 5 to 250 Seconds
DDC, DDC2 monitor	Yes (Max. Resolution: 2048x1536) @ 85Hz	
Hot Swappable	Yes	
Operating systems supported	Windows 98SE/ME/2000/XP/2003 Server, Linux Mac OS9/OSX and Sun Micro System	
Device driver	No Need	
Power	By PS/2 and/or USB or External Power Adaptor (Optional)	
Dimensions (L X W X H)	2-Port : 14.0 x 8.5 x 4.5 cm (5.5 x 3.3 x 1.7 inches)	
	4-Port : 21.5 x 8.8 x 4.5 cm (8.5 x 3.4 x 1.7 inches)	
Unit Weight	2-Port : ~ 450 g	
	4-Port : ~ 650 g	
Housing material	Metal	
Operating Temperature	32~ 122°F (0~ 50°C)	
Humidity	0%~80%RH	

Art.Nr. DC-11202-1	EAN-Nr. 4016032222637	USB-PS/2 Combo-KVM Switch 1User, 2PCs
Art.Nr. DC-12202-1	EAN-Nr. 4016032222644	USB-PS/2 Combo-KVM Switch 1User, 4PCs
Art.Nr. DC-11401-1	EAN-Nr. 4016032222651	USB-PS/2 Combo-KVM Switch 1User, 2PCs with Audio
Art.Nr. DC-12401-1	EAN-Nr. 4016032222668	USB-PS/2 Combo-KVM Switch 1User, 4PCs with Audio