



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## DC-11402

### MINI USB-KVM switch, with audio support - 1User, 2PCS



#### Features

- Control two PCs with one USB keyboard, one USB mouse and one monitor
- Simple installation: No additional software required
- PC selection via hotkey
- LED indicator for monitoring working status of PC and Audio
- Excellent video quality-up to 2048 x 1536, @85HZ
- Support DDC, DDC2, DDC2B, DDC2AB
- Audio support
- Hot plug and play
- Keyboard and mouse emulation for faultless booting of the computer
- Autoscan ( 5,10,20,40,60 sec options)
- No external power supply required
- Integrated KVM cable for connection of two PCs 1.2m
- Support Window 98SE/ME/2000/2003 server/XP/VISTA, Sun Micro , Mac , Linux

#### System requirements

- **Computer:** USB port, VGA port
- **Operating System:** 98SE/ME/2000/2003 server/XP/VISTA, Sun Micro , Mac , Linux

#### Package Contents

- 2 port MINI USB-KVM switch
- User manual
- Quick installation guide

Specification		
Number Of Computers Controlled	2	
Selection Method	USB Keyboard Hot Key, Push Button	
USB Versions supported	1.1	
LEDs	Red for PC Selection Green for PC ON-Line Selection	
PC Connectors	USB	2 x Type A USB Connectors
	Video	2 x HDB-15 male
	Speaker	2 x Stereo speaker plugs
	Microphone	2 x Mono microphone plugs
	KVM Body	1 x DVI 24+5 Connector (male)
Console Ports	Keyboard / Mouse	2 x Type A USB Connectors (female)
	Video	1 x HDB-15 female
	Speaker	1 x Stereo speaker jack
	Microphone	1 x Mono microphone jack
	HOST	1 x DVI 24+5 Connector (female)
Auto-Scan Interval	5,10,20,40,60 Seconds	
DDC, DDC2 monitor	Yes (Max. Resolution: 2048x1536)@85Hz	
Hot Swappable	Yes	
Operating systems supported	Windows 98SE/ME/2000/XP/2003 Server Sun Micro, Mac, Linux	
Device driver	No	
Power	By PC USB power	
Cable Length	1.20 Meter	
Dimensions (LxWxH)	65 x 85 x 25 (mm)	
Unit Weight	450 g	
Housing material	Plastic	
Operating Temperature	32~ 122°F (0~ 50°C )	
Humidity	0%~80%RH	