



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



DC SERIES DEEP CHANNEL CARD GUIDES

Stainless Steel Channel Inserts



Bivar's newly expanded offering of DC Series Deep Channel Card Guides for 1/16th, 3/32nd and 1/8th PCBs are rigid, strong and economical, and meet a wide variety of PCB slot entry applications. The DC Series Deep Channel Card Guides are designed for quick installation, with effective retention and do not require any special tools or fixtures for installation.

FEATURES AND BENEFITS

- 21 Standard lengths from 2-1/2" to 8" in 1/2" increments.
- Three channels widths for 1/16th, 3/32nd and 1/8th PCBs.
- Deep Channel (0.200") for severe duty, high shock and vibration environments.
- Precision molded from 94V-0 UL rated materials for rigidity, strength and heat resistance.
- Stainless steel conductive Inserts available for all sizes.
- Tapered guide entry on pylons allow for easy PCB insertion.
- Recommend panel thickness: 0.047"-0.090" (1.2mm-2.3mm).
- Slotting or elongating of the second and third mounting hole is required to allow for length variations and to provide for easier assembly.
- Material: High quality, precision molded nylon 6/6, flammability characteristic of UL 94V-0.

APPLICATIONS

- For use with System with standardized subracks, that consists of series of slotted cards, which plug into mating connectors on a backplane.
- Ideally suited for use in computer, datacom and telecom applications such as custom enclosures, switches, and blade servers.
- Additionally suitable for use in factory equipment, industrial controls, and defense and military applications.
- Conforms to Eurocard design format.



AVAILABLE OFFERINGS / SPECIFICATIONS

PART NO.	A ±.062 (1.6)	B ±.032 (.8)	C ±.015 (.4)	S.W. ±.005 (.1)	PCB THICKNESS	DESC DWG. NO.
DC-250	2.5 (63.5)	1.5 (38.1)	--	.080 (2.0)	1/16 (1.6)	84101-01
DC-400	4.0 (101.6)	3.0 (76.2)	--			--
DC-450	4.5 (114.3)	3.5 (88.9)	--			84101-02
DC-500	5.0 (127.0)	4.0 (101.6)	--			--
DC-550	5.5 (139.7)	4.5 (114.3)	--			--
DC-600	6.0 (152.4)	5.0 (127.0)	--			84101-03
DC-650	6.5 (165.1)	5.5 (139.7)	--			--
DC-700	7.0 (177.8)	6.0 (152.4)	--			--
DC-750	7.5 (190.5)	6.5 (165.1)	--			--
DC-800	8.0 (203.2)	7.0 (177.8)	3.5 (88.9)			84101-04
DC-400-102	4.0 (101.6)	3.0 (76.2)	--	.102 (2.6)	3/32 (2.4)	--
DC-450-102	4.5 (114.3)	3.5 (88.9)	--			--
DC-500-102	5.0 (127.0)	4.0 (101.6)	--			--
DC-550-102	5.5 (139.7)	4.5 (114.3)	--			--
DC-600-102	6.0 (152.4)	5.0 (127.0)	--			--
DC-650-102	6.5 (165.1)	5.5 (139.7)	--			--
DC-700-102	7.0 (177.8)	6.0 (152.4)	--			--
DC-750-102	7.5 (190.5)	6.5 (165.1)	--			--
DC-800-102	8.0 (203.2)	7.0 (177.8)	3.5 (88.9)			--
DC-450-130	4.5 (114.3)	3.5 (88.9)	--	.132 (3.4)	1/8 (3.2)	84101-22
DC-600-130	6.0 (152.4)	5.0 (127.0)	--			84101-23
DC-800-130	8.0 (203.2)	7.0 (177.8)	3.5 (88.9)			84101-24