# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



### Mobile Magnetic Mount Dual Band Cellular/ DCS and PCS






#### Magnetic Mount Dual Band Antennas

The MDBM dual band mobile antennas provide omnidirectional coverage in cellular and PCS frequencies. They feature a magnetic mount base with protective surface that facilitates secure installation without damage to the vehicle.

#### Features

SMB

- Dual-band design
- Magnetic base for installation on iron base materials
- High roof mounting force
- Protective surface prevents scratches on the vehicle's surface



MDBM800/1900 MDBM824/1850

Electrical Specifications	Mechanical Specifications
VSWR:	Radiator Material:
2.0 across the band (MDBM800/1900)	Stainless steel, black chrome plated
<1.5:1 across each band (MDBM824/ 1850)	Antenna Base:
Polarization:	Molded high strength plastic
Vertical	Mounting Base:
Nominal Impedance:	Black coated stainless steel
50 Ohms	Boot:
Antenna Type:	Rubber
Collinear dual band, closed coil (MDBM800/1900)	Magnet Mounting Force:
Collinear dual band, open coil (MDBM824/1850)	105.8 ounces minimum (MDBM800/ 1900)
Connector Options:	300 ounces minimum (MDBM824/ 1850)
Male SMA	Antenna Height:
Male TNC	14.37" (MDBM800/1900)
Mini-UHF	10.5" (MDBM824/1850)

Model #	Frequency Range	Gain	Cable	List Price
MDBM800/ 1900	824-896/ 1850-1990 MHz	2 dBi @ 824-896 MHz 2 dBi @ 1850-1990 MHz	14' RG58/ U	
MDBM824/ 1850	824-896/ 1850-1990 MHz	2 dBi @ 824-896 MHz 4 dBi @ 1850-1990 MHz	14' RG58/ U	