



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





SERIAL SERVER WITH GALVANIC ISOLATION



DIGI CONNECT[®] ES (EXTENDED SAFETY)

Extended safety terminal server designed for serial over Ethernet applications that require isolation on and between ports

Digi Connect ES provides serial over Ethernet connectivity. It is IEC 60601 3rd Edition compliant and consists of four or eight galvanic isolated RS-232 serial ports, with a 10/100 Mbps network interface and optional Ethernet switch. Digi Connect ES is used in applications that provide Ethernet connections from serial devices to the central data management system.

Galvanic isolation provides extended electrical safety. There is no electrical path for current to earth ground, ensuring no electrical shock when making physical contact with the Digi Connect ES. There is no electrical path from port to port,

ensuring a ground fault will not affect the operation of the Digi Connect ES or the operation of any device connected to it.

Digi's patented RealPort technology makes it possible to establish a connection between the host and a networked serial device by creating a local COM or TTY port on the host computer. Incoming/outgoing and Telnet sessions on each port give system administrators a high level of control over networked serial devices.

BENEFITS

- 4/8-port RS-232 serial-to-network connectivity
- IEC 60601 3rd Edition compliant
- Galvanic isolation on all ports
- Wall mountable
- Patented Digi RealPort[®] technology provides local serial port functionality
- RealPort with encryption available for SSL-based protection for additional security
- Ports may be shared between multiple hosts running different operating systems

APPLICATION EXAMPLE



RELATED PRODUCTS



ConectPort[®] TS




PortServer[®] TS



ConnectPort[®] LTS



Digi Connect[®] Wi-SP



Cables and Accessories

SPECIFICATIONS

Digi Connect® ES

FEATURES

MANAGEMENT	HTTP/HTTPS, CLI or Telnet, Optional secure enterprise management via Digi Remote Manager™
PROTOCOLS	UDP/TCP, DHCP, Extended Telnet RFC 2217, Telnet, Reverse Telnet, Rlogin & Auto Connect, TFTP
SECURITY	SSL, SSL/TLS, SSHv2, FIPS 197 (serial ports), SNMPv2
SOFTWARE	Device-initiated patented RealPort COM port redirector and RFC 2217, Python scripting, Custom development environment
STATUS LEDS	Power, Locator, Serial and Ethernet link/activity
OPERATING SYSTEMS	AIX, HP-UX, Solaris, Linux®, Windows® 2000, Windows® XP, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10, Windows Server® 2003, Windows Server® 2008, Windows Server® 2012. Note: TCP/UDP socket services are operating system independent.
DIMENSIONS (L X W X D)	9.30 in x 10.60 in x 2.10 in (23.5 cm x 26.9 cm x 4.20 cm)
WEIGHT	3.0 lb (1.34 kg)

INTERFACES

SERIAL

PORTS	4/8 separately isolated RS-232 ports (2.5kV)
THROUGHPUT	Up to 230 Kbps
SIGNAL SUPPORT	TXD, RXD, RTS, CTS, DTR, DSR, DCD

ETHERNET

PORTS	1 uplink, Optional 4-port switch
PHYSICAL LAYER	10/100 Base-T separately isolated (1.5kV)
MODE	Full or half duplex

POWER REQUIREMENTS

POWER SUPPLY	Internal 100-240VAC, 50-60 Hz 0.2A max
PRODUCT SURGE PROTECTION (ESD)	4 kV burst (EFT) per EN61000-4-4, 2 kV surge transient per EN61000-4-5 4 kV isolation input to output 2 kV surge per EN61000-4-5

ENVIRONMENTAL

OPERATING TEMPERATURE	0° C to 55° C (32° F to 130° F)
STORAGE TEMPERATURE	-30° C to +85° C (-22° F to +185° F)
RELATIVE HUMIDITY	5 to 95% (non-condensing)
SERIAL PORT PROTECTION (ESD)	15 kV human body model

STANDARDS COMPLIANCE

EMISSIONS	EN 55011, EN 55022, CISPR 11, CISPR 22
SAFETY	EN 60950-1, IEC 60950-1, EN 60601-1, EN 60601-1-2, IEC 60601-1
IMMUNITY	EN 55024, CISPR 24

PART NUMBERS

DESCRIPTION

DC-ES-4SB	Digi Connect ES 4SB - 4 ports
DC-ES-4SB-EU	Digi Connect ES 4SB - 4 ports (International)
DC-ES-4SB-SW	Digi Connect ES 4SB w/ Switch - 4 ports
DC-ES-4SB-SW-EU	Digi Connect ES 4SB w/ Switch - 4 ports (International)
DC-ES-8SB	Digi Connect ES 8SB - 8 ports
DC-ES-8SB-EU	Digi Connect ES 8SB - 8 ports (International)
DC-ES-8SB-SW	Digi Connect ES 8SB w/ Switch - 8 ports
DC-ES-8SB-SW-EU	Digi Connect ES 8SB w/ Switch - 8 ports (International)

DIGI SERVICE AND SUPPORT / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit www.digi.com/support.

© 1996-2015 Digi International Inc. All rights reserved.
All trademarks are the property of their respective owners.

91001320
G1/915

DIGI INTERNATIONAL WORLDWIDE HQ
877-912-3444 / 952-912-3444 / www.digi.com

DIGI INTERNATIONAL FRANCE
+33-1-55-61-98-98 / www.digi.fr

DIGI INTERNATIONAL JAPAN
+81-3-5428-0261 / www.digi-intl.co.jp

DIGI INTERNATIONAL SINGAPORE
+65-6213-5380

DIGI INTERNATIONAL CHINA
+86-21-50492199 / www.digi.com.cn

