



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





EXTENDED SAFETY
WIRELESS ENABLED
TERMINAL SERVER



DIGI CONNECT® WS

Extended safety terminal server is designed for serial over network applications that require 60601 certified solutions

Digi Connect WS is intended to be used with a data acquisition system to connect to RS-232 serial devices and send data from these serial devices to the data acquisition system without adjusting or manipulating the format. The extended safety terminal server complies with IEC 60601-1 3rd edition and can be used in environments requiring this level of testing, including being placed within the patient environment when used as part of a medical electrical (ME) system.

The Digi Connect WS provides serial over IP connectivity for the environment that connects RS-232 devices to an information system network. It is available in three models

with one, four, or eight RS-232 serial ports. Digi Connect WS supports 10/100 Ethernet and 802.11a/b/g/n compatible Wi-Fi.

Independent socket connectivity for each port gives system administrators a high level of control over networked serial devices.


BENEFITS

- 1/4/8-port RS-232 serial-to-network connectivity
- IEC 60601 3rd edition compliant
- Power over Ethernet support
- Wi-Fi Alliance Certified, WPA & WPA2 personal and enterprise, AES, TKIP, 802.11w, 802.11d, 802.11h, PMF
- VESA mountable
- TCP Socket Connectivity to individual devices
- HTTPS supported for additional security
- Ports may be connected to from different systems, OS independent

APPLICATION EXAMPLE



RELATED PRODUCTS



Accessories
and Cables



Enterprise
Support

SPECIFICATIONS

Digi Connect® WS

FEATURE	
MANAGEMENT	HTTPS, HTTP, SNMP, Optional management through Digi Remote Manager SM
PROTOCOLS	HTTP, HTTPS, TCP, SNMP
SECURITY	SSL, TLS
LEDS	Power, Ethernet, Serial, Wi-Fi, Find Me
DIMENSIONS (LENGTH X WIDTH X HEIGHT)	Approximately 200 mm x 160 mm x 40 mm (4 and 8 port), 140 mm x 120 mm x 40 mm (1 port)
WEIGHT	1 kg (4 and 8 port), 0.5 kg (1 port)
MOUNTING	VESA 75, Direct and Arm
INTERFACES	
SERIAL PORTS	1, 4, or 8 ports
SERIAL CONNECTOR	RJ-45 RS232
ETHERNET PORTS	1
ETHERNET PHYSICAL LAYER	10/100
WI-FI	802.11 a/b/g/n 2.4 and 5 g (can be disabled)
WI-FI MODES	Wi-Fi Alliance Cert, WPA & WPA2 personal and enterprise, AES, TKIP, PMF, 802.11d, 802.11h, 802.11w
POWER REQUIREMENTS	
POWER CONSUMPTION	WS 1: 0.1 A RMS MAX WS 4/8: 0.25 A RMS MAX
POWER INPUT	100-240 VAC IEC 60320 C8 Connector
POWER OVER ETHERNET	802.3af
POWER SUPPLY	60601-1 Class II
SURGE PROTECTION	Per IEC 61000-4-5: ±1 kV Per IEC 61000-4-4: ±2 kV for power supply lines (EFT)
ENVIRONMENTAL	
OPERATING TEMPERATURE	+10° C to +40° C
STORAGE TEMPERATURE	-20° C to +40° C
RELATIVE HUMIDITY	10% to 90% non-condensing
ALTITUDE	2000 meters
SERIAL PORT PROTECTION (ESD)	Per IEC 61000-4-2 ±6 kV contact; ±8 kV air
STANDARDS	
SAFETY	EN 60601-1: 2005 + corr.1 (2006) + corr.2 (2007) + A1 :2013, IEC 60601-1-2 Ed3 : 2007, IEC 60601-1-6: 2006 + A1: 2013
EMISSIONS	FCC 47 CFR Part 15 B and C, ICES-003, EN 301489-1, EN 301489-17, EN 300328, EN 62311 Wi-Fi/RF: EN 301 489-1 v1.9.2; EN 301 489-17 v2.1.1; EN 300 328 v1.8.1; EN 62311: 2008; RSS-210
IMMUNITY	EN55024, ICES-003

PART NUMBERS

DESCRIPTION

DC-WS-1-INT	Digi Connect WS, 1 RS232 serial port
DC-WS-4-INT	Digi Connect WS, 4 RS232 serial ports
DC-WS-8-INT	Digi Connect WS, 8 RS232 serial ports

DIGI SERVICE AND SUPPORT / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit www.digi.com/support.

© 1996-2017 Digi International Inc. All rights reserved.
All trademarks are the property of their respective owners.

91003099
A3/717

DIGI INTERNATIONAL WORLDWIDE HQ
877-912-3444 / 952-912-3444 / www.digi.com

DIGI INTERNATIONAL GERMANY
+49-89-540-428-0

DIGI INTERNATIONAL JAPAN
+81-3-5428-0261 / www.digi-intl.co.jp

DIGI INTERNATIONAL SINGAPORE
+65-6213-5380

DIGI INTERNATIONAL CHINA
+86-21-50492199 / www.digi.com.cn

