



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



DVI Connectors



Specification

(DIS) DVI-I Single Link (DDS) DVI-D Single Link
(DID) DVI-I Dual Link (DDD) DVI-D Dual Link

* For digital and analog, please choose DVI-I
* For digital only, please choose DVI-D

Number of Contacts

19, 23, 25, 29... Contacts
Ex. 19 Pin = (19)

Connector Body (Style)

> For Receptacle > For Overmolded with Cable
(P) Front Fastened (A) With Strain Relief

Connector (Housing) Gender

(M) Male Connector (F) Female Connector

Contact Gender

(M) Male (F) Female

Assemble Style

> For Receptacle > For Overmolded with Cable
(S) Solder Type (M) Overmolded with Cable

Mating Style

(S) Screw Thread

Backshell

> For Receptacle > For Overmolded with Cable
(L) Straight / Without Board Lock (L) Straight

Waterproof Rating

(7) IP 67
(8) IP 68

More Information

> For Receptacle > For Overmolded with Cable
(001), (002)..... (□)+(■) : Cable Type + Cable Length
Without Cable : Different Versions EX. (A01) = UL20276 Cable + 1M

(□) : Cable Type (■) : Cable Length
(A) UL20276 From 1M to 5M
28AWG/PVC EX. (01) = 1M