



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




Multilayer Chip Band Pass Filters For 5.0GHz W-LAN

Conformity to RoHS Directive


DEA Series DEA255395BT-2065D2

SHAPES AND DIMENSIONS




RECOMMENDED PC BOARD PATTERNS

LAND



Line width be designed to match 50Ω characteristic impedance depending on PCB material and thickness

SOLDER RESIST



ELECTRICAL CHARACTERISTICS

Item		Minimum value	Typical value	Maximum value
Center frequency	[5395MHz]			
Insertion loss	[4940 to 5850MHz]	(dB)	—	3.5
VSWR	[4940 to 5850MHz]	(dB)	—	2.1
Ripple in pass band	[4940 to 5850MHz]	(dB)	—	2
Attenuation	[DC to 2700MHz]	(dB)	40	—
	[2700 to 4650MHz]	(dB)	24	—
	[7250 to 8000MHz]	(dB)	30	—
Temperature range	Operating	(°C)	-30	+85
	Storage	(°C)	-30	+85


• Ta: -30 to +85°C

• Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.


• All specifications are subject to change without notice.

FREQUENCY CHARACTERISTICS


INSERTION LOSS



ATTENUATION



RETURN LOSS



VSWR

