



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



CHEMTRONICS

Technical Data Sheet

TDS # DEL1692

Flux-Off[®] Delta Flux Remover

PRODUCT DESCRIPTION

Flux-Off[®] Delta Flux Remover is a powerful, nonflammable solvent that removes heavily encrusted and oxidized flux deposits. This product, available as a high pressure aerosol or bulk liquid, penetrates residues quickly to remove all types of flux, production contaminants, oxide particles, dust, grease and oil, then evaporates quickly leaving no residues.


- Powerful cleaning agent
- Non-corrosive, safe for metals
- Nonflammable and fast drying
- Powerful cleaner removes R, RA, RMA, and synthetic fluxes
- Removes encrusted fluxes
- Penetrates to clean hard to reach areas
- Contains no ozone depleting compounds
- All-Way Spray valve - even sprays upside down
- Available with BrushClean[™] System

TYPICAL APPLICATIONS

Flux-Off[®] Delta Flux Remover effectively cleans flux from:

- Chip Carriers
- Heat Sinks
- Metal Housings and Chassis
- Printed Circuit Boards
- Plugs
- Relays and Contacts
- Sockets
- Surface Mount Device Pads
- Switches

TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

Boiling Point	98.6°F Initial	
Evaporation Rate (butyl acetate=1)	>1	
Flash Point (TCC)	None	
Specific Gravity	1.24	
Vapor Pressure @68°F	205 mm Hg	
Appearance	Clear, Colorless Liquid	
Odor	Ethereal	
Solubility in Water	Negligible	
Kauri-Butanol (KB) Number	70	
Surface Tension (dynes/cm @ 73°F)	19	
VOC* Content:	<u>Aerosol</u>	<u>Liquid</u>
CARB	75%	100 %
SCAQMD	484 g/L	645 g/L
Federal	39%	52 %
RoHS Compliant		
Shelflife	Aerosols	5 years
	Liquids	2 years after opening

COMPATIBILITY

Flux-Off[®] Delta is generally compatible with most materials used in the electrical and electronic assemblies, except acrylics, ABS resins, Polycarbonates and Polystyrenes. With any cleaning agent solvent/component compatibility must be determined on a non-critical area prior to use.

<u>Material</u>	<u>Compatibility</u>
ABS	Non-Compatible
Buna-N	Fair
EPDM	Fair
Graphite	Excellent
HDPE	Excellent
LDPE	Good
Lexan™	Fair
Neoprene	Fair
Noryl®	Poor
Nylon™ 66	Excellent
Cross-Linked PE	Excellent
Polypropylene	Excellent
Polystyrene	Non-Compatible
PVC	Excellent
Silicone Rubber	Poor
Teflon™	Excellent
Viton™	Fair

TECHNICAL & APPLICATION ASSISTANCE

Chemtronics provides a technical hotline to answer your technical and application related questions. The toll free number is: **1-800-TECH-401.**

ENVIRONMENTAL IMPACT DATA

ENVIRONMENTAL IMPACT DATA			
HCFC-141b	0.0%	HFC	23.0%
HCFC-225	0.0%	nPB	0.0%

HCFC-225, HCFC-141b, HFC, and nPB percentages shown are the content by weight. HCFC-225, HCFC-141b, HFC, and nPB percentages shown are the content by weight. Hydrochlorofluorocarbons (HCFCs) are regulated under the Montreal Protocol as Class II ozone depleting substances. HCFC-141b is no longer produced in the US under this legislation. HCFC-225 is phased out for production as of 2015. Hydrofluorocarbons (HFCs) are not currently regulated.

Performance	
Rosin Flux removal per gram solvent (mg) / 3 second spray	
Flux-Off Delta	8.3
Competitive AK225 flux remover	7.0

NOTE:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. CHEMTRONICS does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

USAGE INSTRUCTIONS

For industrial use only.
 Read MSDS carefully prior to use.
 Spray 4-6" from surface to clean. Wash parts from top to bottom, allowing the liquid to flush away flux residue. Flux-Off® Delta may be used to remove all types of fluxes in an ultrasonic cleaner.

AVAILABILITY

- DEL1692 12 oz. Aerosol
- DEL892B 6 oz. Brush Clean System
- DEL192 1 Gal. Liquid
- DEL592 5 Gal. Liquid
- DEL5592 53 Gal. Liquid

CHEMTRONICS
 8125 COBB CENTER DRIVE
 KENNESAW, GA 30152
 1-770-424-4888

REV. A (01/15)

<u>DISTRIBUTED BY:</u>