



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



2.4GHz 28.5mm very small stubby WiFi / Bluetooth antenna with SMA male connector

DELTA20/X/SMAM/S/S/35



Features

- Compact direct connect WiFi / Bluetooth antenna
- 28.5mm overall length
- SMA male connector

The Delta 20 is the compact and straight direct connect 2.4GHz stubby antenna at 28.5mm long including the connector. This antenna is available with the SMA male and the Reverse polarity SMA male connectors. The Delta 25 is the right angle version of the Delta 20. This range of very compact 2.4GHz direct connect antennas is likely to be the most popular stubby antennas given their performance and size.

Electrical characteristics:

- Frequency: 2.4~2.5GHz
- VSWR: ≤ 2.0
- Gain: 0dBi
- Polarization: vertical
- Max power: 1 Watt
- Antennna type: 5/8 wave monopole
- Impedance 50 ohms

Mechanical characteristics:

- Antenna length: 28.5mm
- Operating temp: -25 to +70 degrees
- Storage temp: -35 to +70 degrees