## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




Aug.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved. In case that the application demands a high level of reliability, such as automotive, please contact a company representative for further information.



GRAY. STOPPER ANTI-ELECTIFICATION: CLEAFI: STICK SUFFACE PLATING: TIN PLATED 1=m min FINISH . REMARKS CHECKED DATE CHECKED DATE CHECKED DATE 3 - * P - 1. 25H(75)	ELECTIFICATION: C PLATING: TIN PLATED FINISH . RE CHECKED 3662-75- 3662-75-	DC-08: DF13-*		PART NO.	03. 20 03. 19	<del>.</del>
	PLATING:T FINISH FINISH CHE CHE	- 08		DRAWING NO.		:
	PLATING:T FINISH CHE			_	03.20	18.
CATION: CLEAR: STICK IN PLATED 1mm min	PLATING:T F   N   S H		DESIGNED	SIONS	V OF REVI	TION
CATION- CLEAR- STICK	LECTIRIC	JUHFALE	MATERIAL		N0.	
				R. PVC	4 U	
	STOPPER	GRAY.	E E	ELASTOMER	ហ	
				-		
			LINES.	DOTTED L	ICATING	
		ņ	WITHIN 0.1mm.	ITTINGS SHALL BE WITHIN	INGS SHA	i E
		SET	ALL BE	THE LOCK SHALL E TWO LOCKS SH	TACTS, THE OUR, THE TV	A LA
		-	H IS 6mm.	MATED DEPTH		25C. Onta
				<u> </u>	±0.05	A±(
						_
			9 6:04			
				¥		
			 ↓° ₹		H0.2) ±0.1 E±0.05	HO. 2) E ± 0.
				ERN	ράττε	Ē
9	21.9	19.6	23.4	20.4	19.4	
65						
		14.6 15.85	18.4 19.65	15.4 16.65	14.4 15.65	
+ <u>7</u>						
15	13.	10.85	14.65 15 0	11.65 13.0	10.65	
0			13.4	•	9.4	<u> </u>
65		1- 1-		9. 15		
40		7. 10	10. a	7. a	ה ה ה ה ה	_
65	5. D	မ. မာ	7.15	4. 15	3. 15	
		Ш		C	Ξ	

Aug.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved. In case that the application demands a high level of reliability, such as automotive, please contact a company representative for further information.



	END. OWED	P-1.25H(75) P-1.25H(75) P-1.25H(75) P-1.25H(75) P-1.25H(75) P-1.25H(75) P-1.25H(75)	PTS No.   P.1.25H(75) P.1.25H(75)   P.1.25H(75) P.1.25H(75)   P.1.25H(75) P.1.25H(75)   P.1.25H(75) P.1.25H(75)   P.1.25H(75) P.1.25H(75)		
DRAWING PARTO CODE NO. 7	±2mm PER 510mm. QUANTITY OF CON	20 21 22 21 22 21 20 22 20 22 23 28 30 20 20 20 20 20 20 20 20 20 20 20 20 20	QUANTITY OF CONNECTOR 67 57 49 49 39 36 33	ω 4	
EDC-0836 DF13-*P- CL536-	NECTORS IN			ບາ ດາ >1	
3662-75 P-1.25H	TUBE.				
-00 (75)					
	m l	D	0	Φ	Þ