



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



DFB224 - Wrap/Unwrap Bit & Sleeve Set - Data Sheet

This innovative Patented product represents a truly revolutionary approach to wire wrapping, by combining both the wire wrapping and the wire unwrapping functions into one bit/sleeve set. The bit is precision machined for high quality wire wrapping in the clockwise direction, but also includes the removal mechanism that is used to unwrap when operated counterclockwise. The user can quickly and easily switch back and forth between wrap and unwrap mode by retracting or extending the retractable sleeve, and flipping the switch on a PTX Wire Wrapping Power Tool. This product, which can wrap or unwrap 22-24 AWG wire, enables the user to maximize operating efficiency while eliminating the need to purchase and carry extra tools or bits for unwrapping. Also, to prevent pin-to-pin shorting, the retractable wire wrapping sleeve is coated with a durable 1000V dielectric material.



Specifications	
Wrap Function	Wrap, Unwrap
Wrap Type	Regular
Wire Gauge	22-24 AWG (0.65-0.50 mm)
Terminal Hole Dia.	0.075" (1.9 mm)
Terminal Hole Depth	0.50" (12.70 mm)
Maximum Terminal Diagonal	0.073" (1.85 mm)
Minimum Terminal Diagonal	0.054" (1.37 mm)
Effective Radius	0.111" (2.82mm)
Wrap Post Size	0.045" (1.14 mm)
Length	5" (127mm)
Weight	0.134 lbs
UPC No.	811490013902