



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





WRTnode Standard Shield

SKU:DFR0352

This standard shield for WRTnode is directly stackable with the WRTnode Mini OpenWRT Dev Board.

WRTnode (A Mini OpenWRT Dev Board) uses a MTK MT7620N 580MHZ MIPS CPU, and is powerful in both interface and functionality. But expanding its interface with jumper wires is troublesome since there are only pin headers and Micro USB available onboard. This standard shield for WRTnode not only expands GPIO, SPI, I2C, etc., but also expands the number of USB interfaces to four, at the same time providing a 100m Ethernet interface. Now it's your choice to have messy spaghetti or just one shield on your board.

WRTnode (A Mini OpenWRT Dev Board) is a high performance CPU, low power consuming, cheap and small dev board that can run OpenWRT OS and also easy to port all open source software of Linux. OpenWRT is a Linux distribution for embedded devices, the framework to build an application without having to build a complete firmware around it; for users this means the ability for full customization, to use the device in ways never envisioned.

Today, more and more devices could connect to internet, named Internet of Things.

The WRTnode (A Mini OpenWRT Dev Board) is a small node which could connect internet all by itself and do complicated tasks. Such as track a cat running over, identify what you are saying and twitter it, check email and pronounce for you, learn how your room layout and find garbage to sweep while streaming camera video to you over internet. Just to name a few.

Note:



- Be sure to plug the WRTnode into the shield as shown in the picture, Be sure DO NOT go wrong direction.
- For the power we recommend a 5V USB-interface adapter higher than 1000mA, when more USB devices plugged in, we recommend a 2A or 2.5A adapter, such as your ipad one. For WRTnode shield, please check here.

SPECIFICATION

- 5V micro-USB DC-in
- Extend 4 standard USB port
- 1 RJ45 100M Ethernet port(to be a LAN port or WAN port as you define)
- other interfaces:
 - UART
 - I2C(while could multiused as GPIO * 2)
 - SPI
 - GPIO*12
 - Uboot web-page fail-safe de-brick button
 - 5v and 3.3v pins
- Size of layout: 80*48.5*20mm(3.15*1.91*0.79")

SHIPPING LIST

- WRTnode Standard Sheild x1

