



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



DG200 Series | ITE & Medical Safety

200W/400W Peak

- Built-in active PFC
- UL/CSA/EN 60950-1, 2nd edition (ITE)
ANSI/ANMI/CSA/EN 60601-1, 3rd edition (Medical)
- Efficiency: 90% typical
- Operation from -20°C to 65°C - convection
- Approved for 2xMOPP applications
- U-Frame (EU) and enclosed (EC) versions available
- 10 year warranty



GREEN POWER

Description

The **DG200 (ITE)** and **DG200M (Medical) Series** is a 200 Watt Open Frame power supply that is 3"x 5"x 1.42" providing 9.4 Watts per cubic inch. Each unit has a built in Active Power Factor Correction and the efficiency of the series is typically 90% depending on model. The DG200 is compliant with Green power, Energy Star Level VI and ErP EC 1275/2008. The Series is rated at 200 Watts free air convection cooling and up to 300 Watts with 18CFM forced air. This series is available with an optional "U" frame (EU) or covered metal enclosure (EC).

Specifications

Input

Input Voltage	• 90 VAC to 264 VAC, 115/230V nominal
Input Frequency	• 47 Hz to 63 Hz
Inrush Current	• < 30/60A at 115/230 VAC, cold start, 25°C
Power Factor	• >0.9
Input Protection	• Internal T3.15 A / 250 VAC fuse in line
No Load Input Power	• < 0.5W (< 1.5W for "A" version)
Input Current	• 4A max at 115 VAC, 2A max at 230VAC

Output

Output Voltage	• See tables on page 2
Initial Set Accuracy	• See tables on page 2
Minimum Load	• No minimum load required
Start Up Rise Time	• 2 ms typical
Hold Up Time	• > 20 ms typical
Line Regulation	• ±0.5% typical
Load Regulation	• ±1.0% typical
Ripple & Noise	• < 1% pk-pk typical, 20MHz Bandwidth
Overvoltage Protection	• latch off
Overload Protection	• auto recovery
Short Circuit Protection	• auto recovery

Environmental

Operating Temperature	• -20°C to 65°C derating: 3.33% / °C > 50°C
Cooling	• 200W; free air convection 300W; 18CFM forced air
Operating Humidity	• 5-95% RH, non-condensing
Storage Temperature	• -40°C to +85°C
Altitude	• 0 to 3000 m

General

Efficiency	• >90% typical at rated load
Energy Saving	• Energy Star, Level VI
Isolation	• 4000 VAC Input to Output, 2 x MOPP 1500 VAC Input to Ground, 1 x MOPP 1500 VDC Output to Ground, 1 x MOPP
Isolation Resistance	• 50 MΩ
Switching Frequency	• 120 kHz typical
MTBF	• >TBD kWhrs to MIL-HDBK-217F at 50°C

EMC & Safety

Safety Approvals:	• UL/CSA/EN 60950-1, 2nd edition (ITE) • ANSI/AMMI/CSA/EN 60601-1, 3rd edition • CE Mark and CB report
Harmonic Currents	• EN 61000-3-2 class D
EMI	• EN55022 (CISPR 22) Class B, EN 61000-3-3
ESD Immunity	• EN 61000-4-2, 6kV/contact, 8kV/air
Radiated Immunity	• EN 61000-4-3, 10V/m with 80% AM
EFT Burst	• EN 61000-4-4, 2kV
Surge	• EN 61000-4-5, 1kV/L-L, 2kV/L-G
Conducted Immunity	• EN 61000-4-6, 10V with 80% AM
Magnetic Fields	• E61000-4-8, 10A/m
Dips & Interruptions	• EN 61000-4-11, 30% dips 10ms, 60% dips 100ms, 95% dips 5000ms

Warranty

Manufacturer's Warranty	• 10 years. Call Tri-Mag or go to www.Tri-Mag.com for details.
-------------------------	---

DG200 Series | ITE & Medical Safety

Output Specifications

Model No.	Application	Output Rail	Load (A)				Voltage Accuracy	Ripple Noise	Line Reg.	Load Reg.
			Min	Rated	Max	Peak				
DG200(M)-7 DG200(M)-7A	ITE/Medical	+12V	0	16.5	25.0	33.0	+11.9V~+12.1V	<120mVpp	± 0.5%	± 1%
DG200(M)-8 DG200(M)-8A	ITE/Medical	+15V	0	12.0	18.0	22.5	+14.9V~+15.1V	<150mVpp	± 0.5%	± 1%
DG200(M)-3 DG200(M)-3A	ITE/Medical	+18V	0	11.1	16.6	22.3	+17.9V~+18.1V	<150mVpp	± 0.5%	± 1%
DG200(M)-9 DG200(M)-9A	ITE/Medical	+24V	0	8.4	12.5	16.7	+23.9V~+24.1V	<200mVpp	± 0.5%	± 1%
DG200(M)-G DG200(M)-GA	ITE/Medical	+28V	0	7.2	10.7	13.0	+27.9V~+28.1V	<200mVpp	± 0.5%	± 1%
DG200(M)-J DG200(M)-JA	ITE/Medical	+36V	0	5.6	8.3	11.0	+35.8V~+36.2V	<250mVpp	± 0.5%	± 1%
DG200(M)-14 DG200(M)-14A	ITE/Medical	+48V	0	4.2	6.3	8.4	+47.8V~+48.2V	<250mVpp	± 0.5%	± 1%

Notes

- Output Load:**
Convection cooling: 200W; forced-air cooling: 300W max
- Peak Load Duration:**
400W peak rating for durations up to 5 secs. (Duty cycle <10%, avg. power <200W)
- Engineering Specification:**
Contact Tri-Mag for full engineering specification for the specific part number used in your design application.
- Standby Power Consumption with System:**
This is required by ENERGY STAR in U.S. and ErP regulation in Europe for appliances such as computers and displays. The latest requirement is measured input power to be less than 0.5W with system.
- Audible Noise:**
For the DG200(M)-x energy saving series, achieving Level VI (<0.3W) standby power consumption is accomplished through burst mode operation of the controller. The burst operation frequency is dependent on load conditions and is approx. 114Hz, within the audible frequency range.
- Step Efficiency and Average Efficiency:**
Test conditions in step efficiency are referred to 3.2.2 IPS (Internal Power Supply) of the ENERGY STAR program requirements for computers. ENERGY STAR required for efficiency @ 20%, 50%, 100% load is 84.5%, 89% and 86.5%; average efficiency is the average of step efficiency.
- Model Ordering Table:**

Safety/Application	w/o Audible Noise	Energy Saving
ITE	DG200-xA (EU) or (EC)	DG200-x (EU) or (EC)
Medical	DG200M-xA (EU) or (EC)	DG200M-x (EU) or (EC)

- Optional chassis enclosure ordering information:**
U-Frame (EU): DG-200(M)-x(A)EU
Enclosure (EC): DG-200(M)-x(A)EC

Mechanical Specifications

Notes

- Mechanical drawing dimensions in mm Tolerance: ± 0.4mm
- Size: 76.2 x 127 x 36.1 Max. (mm)
3.0 x 5.0 x 1.42 Max. (inches)
- Packing: Net weight: 353 g approx. / unit
- Connections: AC Input: PCB Header: JST B2P3-VH or equivalent
Mating Connector: JST VAR-2, VHR-3N or equivalent
DC Output: PCB Header: JST B8P-VH or equivalent
Mating Connector: JST VHR-8N or equivalent
Terminal Block (optional)
Fan/Remote sense: PCB Header: Molex 22-04-1021 (5045-02A) or equivalent
Mating Connector: Molex 22-01-1022 (5051-02) or equivalent

