



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





GREENLEE.
A Textron Company

MADE FOR THE TRADE!™

DMM, TRMS, AC/DC (DM-510A) (CALIB)

Professional Plant Digital Multimeter



Image
Unavailable

Cat No: DM-510A-C

UPC No: 783310357582

Description

- Measures voltage, current, resistance and frequency
- Tests continuity and diodes
- Backlit LCD with 6,000 count display
- Two voltage detection modes - non-contact or using a single test lead
- BeepJack warns when test leads are incorrectly inserted in current measurement terminals
- Automatic and manual ranges selection
- Relative offset mode to see changes in measurements
- Data hold
- Use optional USB / RS-232 interface DMSC-2U for direct-to-PC logging
- Lifetime Limited Warranty
- Accessories included: (2) 1.5V AAA batteries, bead temperature probe (DM-210A, DM-510A only, 400 DEG F/204 DEG C max), test leads, protective boot
- True RMS for no-compromise accuracy
- Crest capture (peak hold) plus recording of max, min, max-min and average
- Low impedance AutoCheck mode - automatically selects AC or DC volts, resistance or continuity, Low impedance masks ghost voltage pickup
- Measures capacitance
- Measures temperature using a type K thermocouple
- Includes Certificate of Calibration

Specifications

- Amperage Measurement : 600, 6000 MICAMP, 60, 600 MILAMP, 6, 8 AMP
- Battery : (2) 1.5 V AAA
- Capacitance : 60, 600 NFD, 6, 60, 600, 3000MFD
- Display : Backlit LCD With 6,000 Count
- Frequency Measurement : 10 HZ - 50 KHZ Sine Wave, 5 HZ - 999.9 KHZ Logic Level Square Wave
- Includes : (2) 1.5V AAA Batteries, Bead Temperature Probe (DM-210A, DM-510A Only, 400 DEG F/204 DEG C max), Test leads, ProtectiveBoot
- Measurement Category : CAT IV 300 V, CAT III 600 V, CAT II 1000 V
- Replacement Part : TSG-3 Sure-Grip Test Leads
- Resistance Measurement : 600 OHM, 6, 60, 600 KOHM, 6, 60 MOHM
- Standard : CAT IV, CAT III, CAT II, C/ULUS Listed, CE Listed
- Sub Brand : ESM
- Temperature Rating : K Type, -58 To 1832 DEG F (-50 To 1000 DEG C)
- Type : Professional Plant Digital
- Voltage Measurement : 60, 600 MILV, 6, 60, 600, 1000 V