



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





DMM,DLOG 43K,TRMS AC+DC(DML-430A)

Digital Logging Meter (43,000data points)

Cat No: DML-430A

UPC No: 783310087465

Description

- Datalogging Capability - Stores 87,000 Single-Channel Or 43,000 Dual-Channel Measurements
- Use Optional USB InterfaceDMSC-9U To Transfer Data To PC Or For Direct-To-PC logging
- AC+DC True RMS Gives Accurate Readings On Complex Waveforms
- Low Impedance AutoCheck Mode - Automatically Selects AC or DC volts, Resistance Or Continuity
- Low impedance masks ghost voltage pickup
- Backlit LCD Displays 2 Readings With 10,000 Count Resolution
- BeepJack Warns When Test Leads Are Incorrectly Inserted In Current Measurement Terminals
- Measures Voltage, Current,Resistance, Conductance, Frequency And Capacitance
- Checks Continuity And Tests Diodes
- Two Temperature Measurements Using Type K Thermocouples
- Accessories Included: (1)9V Battery, Bead Temperature Probe (400 DEG F / 204 DEG C Max.), Test leads, Protective Boot, Carrying Case
- Lifetime Limited Warranty

Specifications

- Amperage Measurement : 600, 6000 MICAMP, 60, 600 MILAMP, 6, 10 AMP
- Battery : (1) 9 V
- Capacitance : 60, 600 NFDN 6, 60, 600 MFD, 6, 25 MILFD
- Conductance : 99.99 nS
- Display : Backlit LCD Displays 2 Readings With 10,000 Count Resolution
- Frequency Measurement : 15 HZ - 50 KHZ Sine Wave, 5 HZ - 1 MHZ Logic Level Square Wave
- Includes : (1) 9V Battery, Bead Temperature Probe (400 DEG F/204 DEG CMax), Test leads, Protective Boot, Carrying Case
- Measurement Category : CAT IV, 1000 V
- Replacement Part : TC-20 Carrying Case, TSG-3 Sure-Grip Test Leads, TPB Bead Temperature Probe
- Resistance Measurement : 600 OHM, 6, 60, 600 KOHM, 6, 60 MOHM
- Standard : CAT IV, C/UL US Listed, TRUE RMS, CE Listed
- Temperature Rating : K Type, -58 To 1832 DEG F (-50 To 1000 DEG C)
- Type : Digital
- Voltage Measurement : 60.00, 600.0 MILV, 9.999, 99.99, 999.9 V