



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# DIGITUS Server Cabinets

**DN-19 SRV-42U-SW-N**  
**EAN 4016032183488**



The DIGITUS server cabinets are especially suitable for server and switches with high installation depth. The reasoned construction ensures an effectively air circulation and cooling for installed devices. The cabinet can be taken apart for easy entry in small rooms.

#### Logistical Information

Packaging Unit (pcs)	1
Packet weight (kg)	148.4
Box weight in kg	148.4
Country of origin	Turkey

1.5 ? 2mm strong sheet steel with high load capacity, powder coated  
 Side sections detachable and lockable  
 Ventilation slots for active and passive ventilation and exhaustion  
 Protection rating IP 20  
 Perforated front door  
 Perforated two opening back door  
 Opening angle 180° with lockables wing handle  
 Perforated double-wing steel rear doors  
 Spring-mounted hinges enable easy installation of the door or door change  
 3-point locking system, optionally available with cylinder lock  
 Suitable for all server types  
 Up to 1000kg load-bearing capacity  
 Profiles rails on the front and rear sides, adjustable in depth  
 Large cable entry with rubber-edged sliding mechanism on the floor  
 Cable entries on the roof and bottom  
 Height-adjustable levelling feet for the equalisation of uneven floors  
 Tilt-prevention mechanism when pulling out servers  
 Roof module for ventilation unit  
 Inclusive set of 28 assembly screw set  
 Conform to international standards IEC 297-2 and IEC 917-2-1  
 Extensive range of accessories available