



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Side Mounting DTS Series

8000 & 12000 BTU/H



Description

- Designed for side mounting on any enclosure surface where high capacity system cooling is required.
- Closed loop cooling ensures clean enclosure air is recirculated without ever mixing with contaminated ambient air.
- Optimum air circulation with maximum clearance distance between warm inlet and cold outlet for reduced hot spot locations.

Standards

- Maintains enclosure's NEMA 12 rating
- IP 54
- UR, cUR and CE

Features

- R134a refrigerant.
- Thermostat control.
- Hot gas bypass valve prevents evaporator freeze up while minimizing heavy inrush currents on large BTU/H units.
- Built in condensate evaporator.
- Continuous air circulation from high capacity fans.
- EMI/RFI suppression meets CE.
- Self-diagnostics on startup.
- Fault indication via LED light.
- Provision for door contact allowing power down when enclosure door is opened.
- Gasket, mounting kit and template for enclosure cutout and drilling are included.
- Washable filtermat protected within an easily removable grill.
- Condensate drain hose and clamp provided.
- Q Mount allows unit to hang in place for easy installation.
- Versatile design maintains foot print for larger capacity units if required.

Accessories

- Gaskets...see page 400
- Lifting lugs...see page 400
- Remote door switch...see page 400
- Replacement filters...see page 400
- Replacement grill...see page 400

Technical Data

Part Number	Ship Wt. lbs.
DTS8000A115LG	189
DTS8000A230LG	189
DTS12000A115LG	189
DTS12000A230LG	189


Electrical Data	DTS8000A115LG DTS8000A230LG	DTS12000A115LG DTS12000A230LG
Rated Voltage	115 V 60 Hz/ 230 V 50/60 Hz	115 V 60 Hz/ 230 V 50/60 Hz
Range of Operation	103-127 V/187-253 V	103-127 V/187-253 V
Power Consumption	2,100 W/1,800 W	2,300 W/2,000 W
Running Amps	21.0 A/12.5 A	21.0 A/12.5 A
Starting Current	52.0 A/46.2 A	52.0 A/46.2 A
Line Cord	8' Cord	8' Cord

Technical references and DXF downloads available at www.hammf.com


All dimensions in inches unless specified otherwise

Side Mounting DTS Series


8000 & 12000 BTU/H



Front View



Side View



Drilling Template

Climate Control

Refrigeration Data	DTS8000A115LG DTS8000A230LG	DTS12000A115LG DTS12000A230LG
Rated Capacity	8,000 BTU/H (2,340 Watts)	12,000 BTU/H (3,500 Watts)
Type of Refrigerant	R134a	R134a
Refrigerant Charge	750 g	850 g
Adjustable Set Points	Factory setting +95°F (+35°C)	Factory setting +95°F (+35°C)
Max. Ambient Air Temp.	+125°F (+52°C)	+125°F (+52°C)
Min. Ambient Air Temp.	+46°F (+8°C)	+46°F (+8°C)
Air Capacity (unrestricted)	Internal Circulation 450 CFM External Circulation 589 CFM	Internal Circulation 530 CFM External Circulation 589 CFM
Condensate Discharge	Condensate Evaporator	Condensate Evaporator
Filter Mat	150 g/ m ²	150 g/ m ²
Db Noise Level	≤ 69 dB(A)	≤ 69 dB(A)
Unit Weight	160 lbs (72 kg)	165 lbs (75 kg)
Exterior Case	Galvanized sheet steel	Galvanized sheet steel
Finish	RAL7035 Light Grey powder finish	RAL7035 Light Grey powder finish
NEMA Rating	Enclosures IP 54/NEMA 12	Enclosures IP 54/NEMA 12