

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. DIMENSIONS in. STRIP CRIMP COLOR PANDUIT WIRE LENGTH A ±.030 PART NUMBER CODE TOOL RANGE +1/32 +0.8 В .155 .90 CD-800-1. DV18-250MB-3K 22-18 RED - .30 -9/32 (7,1) (22.9)(3.94)CD9-1A (7.6).90 . 175 CD-800-2. DV14-250MB-3K 16-14 BLUE 9/32 (7,1) (22.9)(4,45)CD9-2A .25-.225 .96 CD-800-3. DV10-250M-2K 12-10 YELLOW 11/32 (8.7) (5,71) CD9-3B (6.3)(24.4)NOTES: 1. CSA CERTIFIED FOR: A. 600 V MAX. VOLTAGE RATING B. 300 V MAX. VOLTAGE RATING (DV10-250M-2K) C. 221°F (105°C) MAX. TEMP. RATING * D. STRANDED COPPER WIRE ONLY TERMINAL 10 2. MATERIAL: A. STAMPING - .03" THK COPPER, NICKEL PLATED B. HOUSING - VINYL CARRIER -**HOUS ING** STRIP 3. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS (CONFIGURATION 4. PACKAGE QUANTITY: 3K = 3000 PCS. 2K = 2000 PCS. MAY VARY) CONTINUOUS MOLDED CARRIER STRIP FUNNEL WIRE **ENTRY** CERTIFIED B MAX-LR31212 WIRE INSUL DIA A41406_06 06 | 11/04kLFU ADDED LOGO AND MARKING 10 JAC CCH 1/01 RM $_{
m SKB}$ 08933 FILESPEC WAS N41406AA_PCD-04 05 TINLEY PARK, ILLINOIS MATERIAL WAS TIN PLATED, ADDED CD9 TO CRIMP TOOL COLUMN, NOTE-IC WAS 194°F (90°C) ES 07695 04 DISCO 2 PC. VINYL INSULATED, .250 MALE TAB 10/96 TSMA RLS ADDED DV10-250M-2K LCA DBH 05167 DRAWN BY CHK*D DRAWING NO. A41406 REV BY CHK DESCRIPTION DATE **ECN** CUST NONE JP