



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# BT900 Series

## Bluetooth v4.0 Dual Modules with *smartBASIC*

SMALL. SMART. SIMPLE



Laird's BT900 modules reduce engineering burden and design risk when integrating Bluetooth and Bluetooth Low Energy into any OEM device. A small form factor, optimized power schemes and *smartBASIC* language provide a secure, stable BT environment for any embedded design. Let Laird's innovative BT900 series and decades of expertise in Bluetooth module design speed your product to market.

- **Bluetooth v4.0 dual mode** (BT and BLE)
- Supports **SPP** + any **BLE Peripheral or Central roles**
- Supports **simultaneous BT and BLE** connections
- **Hostless operation** – No need for external MCU reducing overall BOM
- **Broad range of hardware interfaces:** UART, I2C, SPI, ADC, GPIO
- **Small footprint** (19mm x 12.5mm x 2.5 mm)
- ***smartBASIC*** powers rapid design and deployment

### Features at a Glance



#### FLEXIBLE FOR ANY CHALLENGE: A COMPLETE SOLUTION

Cortex M3 microcontroller and *smartBASIC* create truly hostless operation and enable power/throughput flexibility and sleep mode control.



#### SPEED TO MARKET WITH *smartBASIC*

Easily write event-driven apps for any use case and run in the module. No toolchain required.



#### FULL, COMPREHENSIVE BLUETOOTH SOLUTION

The best of Bluetooth: Dual Mode, Simultaneous BT + BLE, and SPP + BLE Peripheral / Central Roles.



#### GLOBAL APPROVALS – MAKE YOURSELF AT HOME

Carries several modular FCC, IC, CE, MIC and Bluetooth SIG approvals



#### PERSONAL SUPPORT FROM DESIGN TO MANUFACTURE

Support works onsite with Laird engineering to speed your design to market.

### Application Areas



Logistics and Barcode Scanners



Point of Sale Terminals



Health and Medical Devices

# BT900 – Bluetooth v4.0 Dual Modules with smartBASIC

Product Brief



## Key Specifications

Category	Feature	Specification	
<b>Wireless Specification</b>	Bluetooth®	V4.0 – Dual-Mode	
	Frequency	2.402 - 2.480 GHz	
	Transmit Power	+ 8 dBm (maximum) Configurable down to -20 dBm	
	Receive Sensitivity	-90 dBm (typical)	
	Link Budget	98 dB	
	Raw Data Rates (Air)	3 Mbps (Classic BT – BR/EDR)	
<b>Host Interface and Peripherals</b>	UART Interface	TX, RX, CTS, RTS, DTR, DSR, DCD, RI can be implemented in smartBASIC-using General Purpose I/O Default 115200, N, 8, 1. From 1200 bps to 921,600 bps	
	Other	GPIO (18 maximum – configurable), I2C (1 configurable from GPIO) SPI (1 from GPIO), ADC (2 from GPIO), Wi-Fi / BT Coexistence (3 dedicated pins)	
<b>Profiles</b>	Bluetooth Low Energy	GATT Client & Peripheral – Any Custom Services	
	Classic Bluetooth	Serial Port Profile (SPP) – Up to 600 kbps	
<b>Programmability</b>	smartBASIC	On-board programming language similar to BASIC	
	smartBASIC application	Via UART or Over the Air	
<b>Control Protocols</b>		Any that can be implemented using smartBASIC vSP – Virtual Serial Port for BLE	
<b>Maximum Connections</b>	Classic Bluetooth	7 clients	
	Bluetooth Low Energy	5 clients	
<b>FW upgrade</b>	smartBASIC engine FW upgrade	Via UART	
<b>Coexistence</b>	802.11 (Wi-Fi)	3 wire CSR schemes supported (Unity-3;Unity-3e)	
<b>Supply Voltage</b>	Supply	1.8V – 3.6V	
<b>Power Consumption</b>	Current	Max Peak Current (@ +8dBm TX) – 85 mA Standby Doze (@ 4MHz) – 2.7 mA Deep Sleep – 233 uA (external signal wake up)	
	Physical	Dimensions	19 mm x 12.5 mm x 2.5 mm      Pad Pitch 0.8 mm
	<b>Environmental</b>	Operating	-40°C to +85°C
Storage		-40°C to +85°C	
<b>Miscellaneous</b>	Lead Free	Lead-free and RoHS compliant	
	Development Kit	Development board and free software tools	
<b>Development Tools</b>	Utilities	Windows, Android, and iOS applications	
<b>Software Tools</b>	Bluetooth®	Complete Declaration ID	
<b>Approvals</b>	FCC / IC / CE / MIC	All BT900 Series	
<b>Warranty</b>		1-Year Warranty	

For full specifications on BT900 modules, please see the BT900 Datasheet (Hardware Integration Guide).

## Did You Know?

LSR, a Laird Business, is a leader in Wireless Product Development, offering true end-to-end solutions through its array of services & technical expertise



### Design Services

- RF Hardware & Antenna Design
- Software/Firmware Development
- Mobile App / Cloud Development
- Industrial Design
- Mechanical Engineering



### EMC Testing & Certification

- On-Site FCC/IC/CE/Giteki/RCM EMC Certification
- Wireless & Antenna Testing
- EMC Emissions Testing
- International Testing Services

CS-Sales@lairdtech.com  
262.375.4400  
www.lsr.com

Contact Sales - Americas: +1 262 375 4400  
Europe: +44 1628 940 ext. 958

Korea: +82 10 2622 3935  
Hong Kong: +852 2923 0610

For documentation, software, sample apps and more visit:  
<http://www.lairdtech.com/products/BT900-Series>