



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Features

- 32-kHz Voltage Regulated Oscillator
- 1.1 V to 2.2 V Operating-voltage Range
- Integrated Capacitors for Digital Trimming
- Suitable for up to 12.5 pF Quartz
- Trimming Inputs Insensitive to Stray Capacitance
- Output Pulse Formers
- Mask Options for Motor Period and Pulse Width
- Low Resistance Output for Bipolar Stepping Motor
- Motor Fast-test Function

## Description

The e1467D is an integrated circuit in CMOS Silicon Gate Technology for analog clocks. It consists of a 32-kHz oscillator, frequency divider, output pulse formers, push-pull motor drivers and alarm output. Integrated capacitors are mask-selectable to accommodate the external quartz crystal. Additional capacitance can be selected through pad bonding to trimming the oscillator frequency.




## 32-kHz Clock CMOS IC with Digital Trimming and Alarm

**e1467D**



## Pad Configuration

Figure 1. Pad Configuration



(1) The pads VDD and OSCOUT are interchangeable per mask option

(2) The pads for ALIN-/MTEST and MOT1L are interchangeable per mask option

## Pin Description

Name	Description
VDD	Positive supply voltage
VSS	Negative supply voltage
OSCIN	Oscillator input
OSCOUT	Oscillator output
MOT1/2	Motor drive outputs
ALIN	Alarm input
ALOUT	Alarm output
SC1 ... SC4	Oscillator trimming inputs

## Functional Description

### Oscillator

An oscillator inverter with feedback resistor is provided to generate the 32768 Hz clock frequency. Values for the fixed capacitors at OSCIN and OSCOUT are mask-selectable (see note 3 of “Operating Characteristics”). Four control inputs, SC1 to SC4, enable the users to add integrated trimming capacitors to OSCIN and OSCOUT, providing 15 tuning steps.

A frequency variation of typically 4 ppm for each tuning step is obtained by bonding the capacitor pads to OSCIN. As none of these pads are bonded, the IC is in an untrimmed state. Figure 2 shows the trimming curve characteristic.

Note: For applications which utilize this integrated trimming feature, Atmel will determine optimum values for the integrated capacitors  $C_{OSCIN}$  and  $C_{OSCOUT}$ .

### Motor Drive Output

The e1467D contains two push-pull output buffers for driving bipolar stepping motors. During a motor pulse, the N-channel device of one buffer and the P-channel device of the other buffer will be activated. Both N-channel transistors are on and conducting between output pulses. The outputs are protected against inductive voltage spikes with diodes to both supply pins. The motor output period and pulse width are mask-programmable, as listed below:

Available motor periods ( $T_M$ ): 125, 250, 500 ms and 2, 16 s

Available maximum pulse widths ( $t_M$ ): 15, 6, 23.4, 31.25, 46.9 ms

Available motor periods for motor test ( $T_{MT}$ ): 250, 500 ms and 1 s

Note: The following constraints for combination of motor period and pulse widths have to be considered:  $T_M > 4 \times t_M$ ,  $T_{MT} > 4 \times t_M$  or alternatively  $T_M = 2 \times t_M$ ,  $T_{MT} = 2 \times t_M$

### Alarm Outputs

The alarm output driver consists of a push-pull stage for driving a speaker via an external bipolar transistor. The output is configured for NPN and PNP bipolar capability. The output is an alarm tone, modulated by a low frequency. Tone frequencies, modulation frequencies, and on/off times are selectable via the metal mask option.


### Alarm Input

A debounced alarm input is provided. Alarm activation is connected either to  $V_{DD}$  or  $V_{SS}$  by a mask option.

### Test Functions

For test purposes, the TEST pad is open. With a high resistance probe ( $R \geq 10 \text{ M}\Omega$ ,  $C \geq 20 \text{ pF}$ ), a test frequency  $f_{TEST}$  of 128 Hz can be measured at the ALIN/MTEST pad. Connecting ALIN/MTEST (for at least 32 ms) to the opposite polarity for alarm activation changes the motor period from the selected value to  $T_{MT}$  (mask-selectable) while the pulse width remains unaffected. This feature can be used for testing the mechanical parts of the clock.

**Figure 2. Functional Test**



## Test Crystal Specification

Oscillation frequency	$f_{OSC} = 32768 \text{ Hz}$
Series resistance	$R_S = 30 \text{ k}\Omega$
Static capacitance	$C_0 = 1.5 \text{ pF}$
Dynamic capacitance	$C_1 = 3.0 \text{ fF}$
Load capacitance	$C_L$ optionally 10 or 12.5 pF

## Absolute Maximum Ratings

Absolute maximum ratings define parameter limits which, if exceeded, may permanently change or damage the device. All inputs and outputs on Atmel's circuits are protected against electrostatic discharges. However, precautions to minimize the build-up of electrostatic charges during handling are recommended. The circuit is protected against supply voltage reversal for typically 5 minutes.

Parameters	Symbol	Value	Unit
Supply voltage	$V_{SS}$	-0.3 to 5 V	V
Input voltage range, all inputs	$V_{IN}$	$(V_{SS} - 0.3 \text{ V}) \leq V_{IN} \leq (V_{DD} + 0.3 \text{ V})$	V
Output short circuit duration		indefinite	
Power dissipation (DIL package)	$P_{tot}$	125	mW
Operating ambient temperature range	$T_{amb}$	-20 to +70	°C
Storage temperature range	$T_{stg}$	-40 to +125	°C
Lead temperature during soldering at 2 mm distance, 10 s	$T_{sld}$	260	°C

## Operating Characteristics


$V_{SS} = 0\text{ V}$ ,  $V_{DD} = 1.5\text{ V}$ ,  $T_{amb} = +25^{\circ}\text{C}$ , unless otherwise specified.

All voltage levels are measured with reference to  $V_{SS}$ . Test crystal as specified below.


Parameters	Test Conditions	Symbol	Min.	Typ.	Max.	Unit
Operating voltage		V <sub>DD</sub>	1.1	1.5	2.2	V
Operating temperature		T <sub>amb</sub>	-20		+70	°C
Operating current	R <sub>1</sub> = ∞ <sup>(2)</sup>	I <sub>DD</sub>		1	3	μA
Motor Drive Output						
Motor output current	V <sub>DD</sub> = 1.2 V, R <sub>1</sub> = 200 Ω	I <sub>M</sub>	±4.3			mA
Motor period		T <sub>M</sub>	See option list			s
Motor period during motor test		T <sub>MT</sub>	See option list			ms
Motor pulse width		t <sub>M</sub>	See option list			ms
Oscillator						
Start-up voltage	Within 2 s	V <sub>START</sub>	1.2		2.2	V
Frequency stability	ΔV <sub>DD</sub> = 100 mV, V <sub>DD</sub> = 1.1 to 2.2 V	Δf/f		0.1	0.2	ppm
Integrated input capacitance	<sup>(3)</sup>	C <sub>OSCIN</sub>	See option list			pF
Integrated output capacitance		C <sub>OSCOUT</sub>	See option list			pF
Input current SC1 to SC4	V <sub>IN</sub> = 0.2 V V <sub>IN</sub> = V <sub>DD</sub> <sup>(5)</sup>	I <sub>SCINL</sub>	1	5	25	μA
		I <sub>SCINH</sub>	0.05	0.15	0.5	μA
Alarm/Output						
Output current for driving npn transistor	V <sub>DD</sub> = 1.2 V					
N-channel	R <sub>3</sub> = 100 kΩ	I <sub>ANn</sub>	1	3	10	μA
P-channel	R <sub>2</sub> = 1 kΩ <sup>(2)(4)</sup>	I <sub>ANp</sub>	-0.5	-1		mA
Output current for driving pnp-transistor	V <sub>DD</sub> = 1.2 V					
N-channel	R <sub>3</sub> = 1 kΩ	I <sub>APn</sub>	0.5	1		mA
P-channel	R <sub>2</sub> = 100 kΩ <sup>(2)(4)</sup>	I <sub>APp</sub>	-1	-2	-10	μA
Alarm Options						
Tone frequency		f <sub>A</sub>	See option list			Hz
Modulation frequency		f <sub>MOD</sub>	See option list			Hz
On/off time		t <sub>ON</sub> /t <sub>OFF</sub>	See option list			s
Alarm Input/Motor Test						
Input current	ALIN = V <sub>DD</sub> , peak current	I <sub>AINH</sub>	0.6	3	10	μA
Input current	ALIN = V <sub>SS</sub> , peak current	I <sub>AINL</sub>	-0.6	-3	-10	μA
Input debounce delay		t <sub>AIN</sub>	23.4		31.2	ms

- Notes:
1. Typical parameters represent the statistical mean values
  2. See test circuit
  3. Values can be selected in 1 pF steps. A total capacitance ( $C_{OSCIN} + C_{OSCOU}$ ) of 38 pF is available
  4. NPN or PNP driving transistors defined by mask options
  5.  $I_{SCINH}$  is the peak current of a pulsed current with a duty cycle of 1:63. Average current is always smaller than 10 nA


**Figure 3.** Motor Output Signal During Normal Operation and During Motor Test



**Figure 4.** Alarm Operation



**Figure 5.** Typical Trimming Curve Characteristic for  $T_M$  of 2 s



$C_{OX}$  means frequency deviation due to production process variations.

Trimming inputs SC1 ... SC4 are binary weighted, i.e.,

SC1 ... SC4 = 0 corresponds to trimming step 0

SC1 ... SC4 = 1 corresponds to trimming step 15

LSB = SC1

## Ordering Information

**Table 1.** Option List e1467D

Option	Motor			Alarm					Load Cap.	Integrated Capacitance	
	Cycle (T <sub>M</sub> ) s	Pulse (t <sub>M</sub> ) ms	Test (T <sub>MT</sub> ) ms	Frequency Hz	Modulation Frequency Hz	On/off Time s	Driver Type	Activation Polarity	pF	C <sub>OSCIN</sub> <sup>(1)</sup> pF	C <sub>OSCOUT</sub> <sup>(1)</sup> pF
-B	2	23.4	250	2048	8	0.5/0.5	NPN	V <sub>SS</sub>	10	17	12
-D	2	31.25	250	2048	8	0.5/0.5	NPN	V <sub>DD</sub>	10	17	12
-V2	0.5	23.4	250	2048	8	0.5/0.5	NPN	V <sub>SS</sub>	12.5	20	16
E2	2	46.9	250	2048	8	1/3	NPN	V <sub>SS</sub>	12.5	20	16

Note: 1. On-chip stray capacitance included

Option	Pad Designation												
	Pad 1	Pad 2	Pad 3	Pad 4	Pad 5	Pad 6	Pad 7	Pad 8	Pad 9	Pad 10	Pad 11	Pad 12	Pad 13
-B	OSCIN	V <sub>DD</sub>	ALOUT	MOT2	MOT1	MOT1	ALIN/MTEST	V <sub>SS</sub>	OSCOUT	SC4	SC3	SC2	SC1
-D	OSCIN	OSCOUT	ALOUT	MOT2	MOT1	MOT1	ALIN/MTEST	V <sub>SS</sub>	V <sub>DD</sub>	SC4	SC3	SC2	SC1
-V2	OSCIN	V <sub>DD</sub>	ALOUT	MOT2	MOT1	MOT1	ALIN/MTEST	V <sub>SS</sub>	OSCOUT	SC4	SC3	SC2	SC1
-D	OSCIN	OSCOUT	ALOUT	MOT2	MOT1	ALIN/TEST	MOT1	V <sub>SS</sub>	V <sub>DD</sub>	SC4	SC3	SC2	SC1



## Atmel Corporation

2325 Orchard Parkway  
San Jose, CA 95131  
Tel: 1(408) 441-0311  
Fax: 1(408) 487-2600

## Regional Headquarters

### Europe

Atmel Sarl  
Route des Arsenaux 41  
Case Postale 80  
CH-1705 Fribourg  
Switzerland  
Tel: (41) 26-426-5555  
Fax: (41) 26-426-5500

### Asia

Room 1219  
Chinachem Golden Plaza  
77 Mody Road Tsimshatsui  
East Kowloon  
Hong Kong  
Tel: (852) 2721-9778  
Fax: (852) 2722-1369

### Japan

9F, Tonetsu Shinkawa Bldg.  
1-24-8 Shinkawa  
Chuo-ku, Tokyo 104-0033  
Japan  
Tel: (81) 3-3523-3551  
Fax: (81) 3-3523-7581

## Atmel Operations

### Memory

2325 Orchard Parkway  
San Jose, CA 95131  
Tel: 1(408) 441-0311  
Fax: 1(408) 436-4314

### Microcontrollers

2325 Orchard Parkway  
San Jose, CA 95131  
Tel: 1(408) 441-0311  
Fax: 1(408) 436-4314

La Chantryerie  
BP 70602  
44306 Nantes Cedex 3, France  
Tel: (33) 2-40-18-18-18  
Fax: (33) 2-40-18-19-60

### ASIC/ASSP/Smart Cards

Zone Industrielle  
13106 Rousset Cedex, France  
Tel: (33) 4-42-53-60-00  
Fax: (33) 4-42-53-60-01

1150 East Cheyenne Mtn. Blvd.  
Colorado Springs, CO 80906  
Tel: 1(719) 576-3300  
Fax: 1(719) 540-1759

Scottish Enterprise Technology Park  
Maxwell Building  
East Kilbride G75 0QR, Scotland  
Tel: (44) 1355-803-000  
Fax: (44) 1355-242-743

### RF/Automotive

Theresienstrasse 2  
Postfach 3535  
74025 Heilbronn, Germany  
Tel: (49) 71-31-67-0  
Fax: (49) 71-31-67-2340

1150 East Cheyenne Mtn. Blvd.  
Colorado Springs, CO 80906  
Tel: 1(719) 576-3300  
Fax: 1(719) 540-1759

### Biometrics/Imaging/Hi-Rel MPU/

### High Speed Converters/RF Datacom

Avenue de Rochepleine  
BP 123  
38521 Saint-Egreve Cedex, France  
Tel: (33) 4-76-58-30-00  
Fax: (33) 4-76-58-34-80

---

### e-mail

[literature@atmel.com](mailto:literature@atmel.com)

### Web Site

<http://www.atmel.com>

**Disclaimer:** Atmel Corporation makes no warranty for the use of its products, other than those expressly contained in the Company's standard warranty which is detailed in Atmel's Terms and Conditions located on the Company's web site. The Company assumes no responsibility for any errors which may appear in this document, reserves the right to change devices or specifications detailed herein at any time without notice, and does not make any commitment to update the information contained herein. No licenses to patents or other intellectual property of Atmel are granted by the Company in connection with the sale of Atmel products, expressly or by implication. Atmel's products are not authorized for use as critical components in life support devices or systems.

© Atmel Corporation 2003. All rights reserved.

Atmel® and combinations thereof are the registered trademarks of Atmel Corporation or its subsidiaries.

Other terms and product names may be the trademarks of others.



Printed on recycled paper.