



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Core **E35/18/10**



Effective parameters			
	Parameter	Value	Unit
$\Sigma(I/A)$	core factor (C1)	0.807	mm ⁻¹
Ve	effective volume	8070	mm ³
Le	effective length	80.7	mm
Ae	effective area	100	mm ²
Amin	minimum area	100	mm ²
m	E35/18/10	≈ 20	g/pcs

Dimensions for product: E35/18/10						
	Nom	Tol +	Tol -	Max	Min	Unit
A	35.00	0.50	0.50	35.50	34.50	mm
B					24.50	mm
C	10.00	0.30	0.30	10.30	9.70	mm
D	17.50	0.25	0.25	17.75	17.25	mm
E	12.50	0.25	0.25	12.75	12.25	mm
F	10.00	0.30	0.30	10.30	9.70	mm

Inductance factor					
Material	Value	Tol +	Tol -	Unit	
3C94	2500	25%	25%	nH/turns ²	
3C95	2980	25%	25%	nH/turns ²	
3F36	1800	25%	25%	nH/turns ²	

Power loss: 3C94					
Measuring conditions			Max	Unit	
100 kHz	200 mT	100 °C	4.000	W/set	
Power loss: 3C95					
Measuring conditions			Max	Unit	
100 kHz	200 mT	100 °C	3.900	W/set	
100 kHz	200 mT	25 °C	4.200	W/set	
Power loss: 3F36					
Measuring conditions			Max	Unit	
500 kHz	50 mT	100 °C	1.200	W/set	
500 kHz	100 mT	100 °C	9.300	W/set	

Core **E35/18/10**

Bsat					
Measuring conditions			Material	Min	Unit
25 kHz	250 A/m	100 °C	3C94	320	mT
25 kHz	250 A/m	100 °C	3C95	330	mT
25 kHz	250 A/m	100 °C	3F36	340	mT