

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Four Channel SLT E3T-MICFP-40

The Four Channel SLT converts almost any switch or contact closure into a wireless contact transmitter, allowing wireless control of distant loads in up to four zones: lights, motors, pumps, fans, fountains, and signage.

The Four Channel SLT also adds wireless control extension to timers, automation controllers, load-shedding controllers, and dry contact devices.

Easy-To-Use

- Installs in minutes
- · Easy-to-configure
- · Requires no switch leg wires
- · Communicates with ILLUMRA receivers

Reliable Range

- 50-150 foot range
- · Repeaters available for added range

Save Time and Money

The new sensor reduces cost by eliminating expensive materials and eliminating tedious and time-consuming labor. The SLT wireless sensor can control an unlimited number of ILLUMRA wireless receivers. Each ILLUMRA wireless receiver responds to up to 30 different SLT wireless sensors.

The SLT wireless sensor is manufactured to the latest quality standards in an ISO 9001:2000 facility, is ROHS compliant, and is FCC and IC approved.



T: 801.349.1200 F: 801.653.4257

sales@illumra.com



Buildings using the SLT wireless sensor and other Illumra products:

- · Qualify for LEED credits
- · May qualify for Energy-Star ratings
- Require fewer materials and less labor during installation
- · Have the ability to use less energy.

	E3T-MICFP-40
Range	50-150 feet (typical)
Frequency	315 MHz
Power Supply Input Rating	8-28 VDC, 40 mA
Inputs	30 VDC max, 100 mA max
Input Threshold Voltage Levels	Input Low Voltage: <1VDC Input High Voltage: 3VDC <vin<30vdc< th=""></vin<30vdc<>
Channels	4 inputs
Operating Temperature	-13° to 140°F (-25° to +60°F)
Storage Temperature	-40°F to 140°F (-40°F to +60°F)
Dimensions	2.88"(W) x 1.30"(H) x 0.67"(D) 7.32cm x 3.30cm x 1.70cm
Antenna	attached whip antenna (5.85")
Radio Certification	FCC (United States) SZV-TCM2XXC I.C. (Canada) 5713A-TCM2XXC
Addressing	Factory set unique ID (1 of 4 billion)



