



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Core **E55/28/21**



Effective parameters			
	Parameter	Value	Unit
$\Sigma(I/A)$	core factor (C1)	0.35	mm <sup>-1</sup>
<b>Ve</b>	effective volume	44000	mm <sup>3</sup>
<b>Le</b>	effective length	124	mm
<b>Ae</b>	effective area	353	mm <sup>2</sup>
<b>Amin</b>	minimum area	345	mm <sup>2</sup>
<b>m</b>	E55/28/21	≈ 108	g/pcs

Dimensions for product: E55/28/21						
	Nom	Tol +	Tol -	Max	Min	Unit
<b>A</b>	56.20	0.00	2.10	56.20	54.10	mm
<b>B</b>	37.50	1.50	0.00	39.00	37.50	mm
<b>C</b>	17.20	0.00	0.50	17.20	16.70	mm
<b>D</b>	27.50	0.30	0.30	27.80	27.20	mm
<b>E</b>	18.50	0.80	0.00	19.30	18.50	mm
<b>F</b>	21.00	0.00	0.80	21.00	20.20	mm

Inductance factor					
Material	Value	Tol +	Tol -	Unit	
3C91	8625	25%	25%	nH/turns <sup>2</sup>	
3C92	4700	25%	25%	nH/turns <sup>2</sup>	
3C94	6400	25%	25%	nH/turns <sup>2</sup>	
3C95	8625	25%	25%	nH/turns <sup>2</sup>	
3F36	4200	25%	25%	nH/turns <sup>2</sup>	

Power loss: 3C91					
Measuring conditions			Max	Unit	
100 kHz	200 mT	60 °C	22.000	W/set	
Power loss: 3C92					
Measuring conditions			Max	Unit	
100 kHz	200 mT	100 °C	22.000	W/set	
Power loss: 3C94					
Measuring conditions			Max	Unit	
100 kHz	200 mT	100 °C	22.000	W/set	

## Core **E55/28/21**

Power loss: 3C95				
Measuring conditions			Max	Unit
100 kHz	200 mT	100 °C	21.000	W/set
100 kHz	200 mT	25 °C	23.000	W/set
Power loss: 3F36				
Measuring conditions			Max	Unit
500 kHz	50 mT	100 °C	10.000	W/set
500 kHz	100 mT	100 °C	64.000	W/set

Bsat					
Measuring conditions			Material	Min	Unit
25 kHz	250 A/m	100 °C	3C91	320	mT
25 kHz	250 A/m	100 °C	3C92	370	mT
25 kHz	250 A/m	100 °C	3C94	320	mT
25 kHz	250 A/m	100 °C	3C95	330	mT
25 kHz	250 A/m	100 °C	3F36	340	mT

Accessories		
Ordering name	Description	Ordering code
CLA-E55/28/21	Clasp	431202126091
CP-E55/28/21-1S	Coil former, termoplastic	431202128713
CP-E55/28/21-1S-A	Coil former, termoplastic	433500027031
CPH-E55/28/21-1S-22P-Z	Coil former, termoplastic, horizontal	432202106791
SPR-E55/28/21	Spring	431202126131