



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Link Analyzer

E3X-P30

E8X-P30

The Link Analyzer allows specifiers and installers to plan, verify and maintain EnOcean based wireless networks. The hand-held analyzer is available in 315MHz and 868MHz versions.

With a large backlit LCD display that is easy to read even under difficult lighting conditions, the P30 is a great tool for creating EnOcean based control networks.

The analyzer has four analyzer modes that test links, repeaters, and networks and also includes the ability to remotely control EnOcean based products. Power is supplied from two "AA" batteries. A wide-range AC power supply, including a USB plug, comes with the P30, which allows long-term logging of the radio channel, including: timing, signal strength, and packet data.

The P30 can communicate with PC's via USB. WinEtel and Dolphin View tools from EnOcean are supported for development engineers and field application experts. USB drivers are available for Windows, Linux and Mac OS-X.



Four Modes for Easy Analysis

- Radio Network Analysis
- Repeater Analysis
- Radio Link Test
- Remote Management

	E3X-P30, 315 MHz - E8X-P30, 868 MHz
Range	50-150 feet
Power Supply	Battery or external power supply
Frequency	315 MHz or 868 MHz