



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## Product information Configurable Industrial Security-Router - EagleOne-0200T1T1SDDY90000HHE05.3.

Industrial Ethernet:Industrial Firewall System:EAGLE One:Configurable Industrial Security-Router	
<a href="https://www.e-catalog.beldensolutions.com/443/link/57078-24455-49853-401129-400975/en/EagleOne-0200T1T1SDDY90000HHE05.3./uistate">https://www.e-catalog.beldensolutions.com/443/link/57078-24455-49853-401129-400975/en/EagleOne-0200T1T1SDDY90000HHE05.3./uistate</a>	
Name	Configurable Industrial Security-Router
	
	Industrial firewall and security router with extensive Layer 2 and Layer 3 redundancy features, DIN rail mounted, fanless design.
Delivery informations	
Availability	available
Product description	
Description	Industrial firewall and security router with extensive Layer 2 and Layer 3 redundancy features, DIN rail mounted, fanless design.
Port type and quantity	2 ports in total, Ports Fast Ethernet: 2 x 10/100 Mbit/s
Type	EagleOne-0200T1T1SDDY90000HHE05.3.
Order No.	EagleOne-0200T1T1SDDY90000HHE05.3.
More Interfaces	
Power supply/signaling contact	1 x plug-in terminal block, 6-pin
Digital Input	1 x plug-in terminal block, 2-pin
V.24 interface	1 x RJ11 socket
USB interface	1 x USB to connect the AutoConfiguration Adapter ACA21-USB EEC
Network size - length of cable	
Twisted pair (TP)	0 m ... 100 m
Network size - cascading	
Line - / star topology	any
Power requirements	
Operating voltage	12/24/48 VDC/24 VAC (redundant)
Power consumption	6.9 W
Software	
Stateful inspection firewall	Firewall rules (incoming/outgoing, management), DoS prevention, MAC filter, user firewall for external activation of FW rules
Management	SNMPv3, SSH2/SFTP, HTTPS, V.24 CLI, central user management (RADIUS), SSH1, SNMPv1/2, HiDiscovery, Industrial HiVision, HiView
Multipoint VPN	Point to point, point to multipoint, remote enable/disable or via digital input, IPsec, IKEv1/v2, 3DES, AES (-128, -192, -256), Pre-Shared Key, X.509v3 certificates, MD5, SHA-1, NAT-T
Diagnostics	LLDP, LEDs (status, VPN, redundancy, link status, data, ACA), signal contact, logfile, syslog, configuration check
Configuration	Web based GUI, SNMPv3, CLI, Automatic configuration roll-back, text based configuration file, offline configuration, HiView
Security	HTTPS, SSHv2, SFTP, SNMPv3, Management VLAN, Role based Access
Routing	Static routing, multinetting, IP masquerading, 1-to-1 NAT, port forwarding.
Redundancy functions	Use in redundant networks/ring coupling, firewall redundancy (layer 4)
Time synchronisation	NTP/SNTP
Miscellaneous	DHCP Server/Client, DHCP Relay/Option 82, DynDNS, PPP, PPPoE, VLAN-Support , packet capture (pcap Format)
Ambient conditions	
Operating temperature	0 °C ... 60 °C
Storage/transport temperature	-40 °C ... 85 °C
Relative humidity (non-condensing)	10 % ... 95 %
Mechanical construction	
Dimensions (W x H x D)	60 mm x 145 mm x 125 mm
Mounting	DIN Rail
Weight	660 g
Protection class	IP20
Approvals	
Basis Standard	CE, FCC, C-Tick, EN61131, EN 60950-1 ,

**Industrial Ethernet:Industrial Firewall System:EAGLE One:Configurable Industrial Security-Router**

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-49853-401129-400975/en/EagleOne-0200T1T1SDDY90000HHE05.3./ui/state>

<b>Safety of information technology equipment</b>	cUL 508
<b>Scope of delivery and accessories</b>	
<b>Scope of delivery</b>	Device, terminal blocks, operating instructions, manual on CD
<b>Accessories to order separately</b>	Rail power supply RPS 30, RPS 80 EEC, RPS 120 EEC, terminal cable, network management Industrial HiVision, auto-configuration adapter ACA21-USB EEC, 19" installation frame

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.