



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



EB-9000S-2 CURIE HEAT TECHNOLOGY SOLDERING/REWORK STATION

EB-9000S-2 FEATURES

- LCD display showing power demand from tip
- A slim soldering handpiece with comfortable grip and unique design for achieving a balanced “tip to grip” ratio.
- Improved cartridge design to ensure optimum tip performance and recovery.
- Increased plating to balance tip life and performance
- Gold plated connector for higher conductivity
- Color bands that provide for easy temperature identification and assist in audit and inventory control.
- Two switchable soldering ports
- Certified in accordance with TUV, CE & GS standards.

WARRANTY

All equipment and accessories are warranted to be free from defects in materials and workmanship:

Part Number	Description	Warranty Period
EB-9000PS-2	220-240V Power Supply	4 Years
SHP-1	Handpiece	90 Days
SHH-1	Workstand	90 Days



EB-9000S-2 COMPONENTS

EB-9000PS-2	Power Supply
SHH-1	Soldering Handpiece Holder
SHP-1	Soldering Handpiece
RMP-1	Tip Removal Pad
SG-1-GR	Handpiece Grip Green
SG-1-GY	Handpiece Grip Gray
BC-1	Brass Curls
SPG-1	Sulphide Free Sponge
EBM8CH176	Soldering tip cartridge

EB-9000S SPECIFICATIONS

Input Line Voltage:	EB-9000S-2	220-240 VAC
Tip to Ground Potential:		<2mV, true RMS 50-500Hz
Tip to Ground Resistance:		<2 Ohms DC
Idle temperature Stability:		+/- 1.1°C (2°F)
Ambient Operating Temperature:		10-40°C (50°F -104°F)
Maximum Enclosure Temperature:		50°C (122°F)
Fuse:	EB-9000S-2	250V 0.5A
Output Power (Maximum):		40 Watts
Output Frequency:		13.56 MHz
Size (W x H x D):		212.4mm x 118mm x 132mm
Weight:		3.47 KG
LCD display:		60mm x 16mm
Input Line Frequency:		50/60 Hz
Certification marks:		CE, GS

