imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Data Sheet EB01-6MBI 450U4-170 Basic Board for Fuji High-Power 6-Pack Modules 6MBI 450U4-170

Abstract

The EB01-6MBI450U4-170 is a basic board to be used with six-channel driver 6SD312EI for reliable driving and safe operation of Fuji IGBT modules 6MBI450U4-170.

The basic board EB01-6MBI450U4-170 (with driver 6SD312EI) is fully matched to IGBT module 6MBI450U4-170. Its plug-and-play capability makes it ready to operate immediately after mounting. The user needs invest no effort in designing or adjusting it to a specific application.

Product Highlights Plug-and-play solution Suitable for 6MBI450U4-170 No electrolytic capacitors Extremely reliable; long service life Shortens application development time Motor drives Wind-power converters Welding SMPS

and many others



Important: Please refer to the relevant manuals!

This data sheet contains only product-specific data for the basic board. Information specific to the relevant driver can be found in the corresponding data sheet.

A detailed description, must-read application notes and general data applicable to this driver family are found in: "Description and Application Manual, Six-Channel Driver 6SD312El for the EconoPACK+ Modules ".

Dimensions

Dimensions: 162 x 100 mm.

Height including driver: 21 mm (30 mm with connector X1 and flat cable).

Mounting principle: soldered onto a High-Power 6-Pack IGBT module 6MBI450U4-170.

Absolute Maximum Ratings					
Parameter	Remarks	Min Max	Units		
Input power per channel	Note 1	3	W		
Switching frequency	Note 2	35	kHz		
DC link voltage	Note 3	1200	V		
Operating temperature		-40 +85	°C		
Storage temperature		-40 +90	°C		

All data refer to + 25°C unless otherwise specified



Electrical Characteristics

Short-circuit protection	Remarks	Min Typ. Max	Units
V _{ce} -monitoring threshold Response time	Betw. aux. terminals Note 4	3.65 11.3	V μs
Gate output	Remarks	Min Typ. Max	Units
Turn-on gate resistor $R_{g(on)}$ Turn-off gate resistor $R_{g(off)}$		1.2 6.8	Ω Ω
Electrical insulation	Test conditions	Min Typ. Max	Units
Creep path between channels	9	mm	
All data refer to 25°C uplace	otherwise encoified		

All data refer to +25°C unless otherwise specified

Footnotes to the key data

- 1) The input power is limited by the on-board gate resistors.
- 2) If the specified max. switching frequency is exceeded, the gate resistors may overheat.
- This limit is due to active clamping. Refer to the "Description and Application Manual, Six-Channel Driver 6SD312EI for the EconoPACK+ Modules".
- 4) Pulse width of the direct output of the gate drive unit (excluding the gate-resistor delay).

Important Notice

The data contained in this product data sheet is intended exclusively for technically trained staff. Handling all high-voltage equipment involves risk to life. Strict compliance with the respective safety regulations is mandatory!

Any handling of electronic devices is subject to the general specifications for protecting electrostatic-sensitive devices according to international standard IEC 747-1, Chapter IX or European standard EN 100015 (i.e. the workplace, tools, etc. must comply with these standards). Otherwise, this product may be damaged.

Disclaimer

This data sheet specifies devices but cannot promise to deliver any specific characteristics. No warranty or guarantee is given – either expressly or implicitly – regarding delivery, performance or suitability.

CT-Concept Technologie AG reserves the right to make modifications to its technical data and product specifications at any time without prior notice. The general terms and conditions of delivery of CT-Concept Technologie AG apply.



Ordering Information

The general terms and conditions of delivery of CT-Concept Technologie AG apply.

Related I GBT	CONCEPT Driver Type #
Fuji 6MBI450U4-170	6SD312EI
Connection	CONCEPT Modular Cable Type #
6SD312EI to EB01-6MBI450U4-170	MIC01A (6 items per driver)
Related I GBT	CONCEPT Basic Board Type #
Fuji 6MBI450U4-170	EB01-6MBI450U4-170

Information about Other Products

For drivers adapted to other high-voltage or high-power I GBT modules

Direct link: www.IGBT-Driver.com/go/plug-and-play

For other drivers and evaluation systems

Please click: www.IGBT-Driver.com

© Manufacturer

CT-Concept Technologie AG Intelligent Power Electronics Renferstrasse 15 CH-2504 Biel-Bienne Switzerland

Tel. + 41 - 32 - 344 47 47 Fax + 41 - 32 - 344 47 40

E-mail <u>Info@IGBT-Driver.com</u> Internet <u>www.IGBT-Driver.com</u>

© Copyright 1998...2008 by CT-Concept Technologie AG - Switzerland. All rights reserved. We reserve the right to make any technical modifications without prior notice. Version of 2016-05-20

IGBT-Driver.com