



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# VRLA Rechargeable Battery

## EB20-12



### FEATURES

- Absorbent Glass Mat technology for efficient gas recombination
- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Can be used in any orientation(excluding used inverted)
- The battery is designed for high power & high cyclic usage
- Low self-discharge rate, lower than 3% capacity loss per month

### APPLICATION

- UPS
- E-bike
- Wheelchairs
- Lawn Mowers
- Golf-Carts
- Electrical Scooter



### SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	20Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	6450g(14.22lbs.)
Terminals	B1 (Fitting M5 bolt & nut) I1 is optional
Internal Resistance	≤ 11mΩ (Fully Charged )
Max. Discharge Current	300 A (5 sec.)
Max. Charge Current	6.0 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	Standard: ABS( UL 94-HB) EB20-12 Optional: Flame Retardant ABS(UL 94-V0) EB20-12FR



- IEC 61056-1
- JIS C 8702-1
- GB/T 19639.1

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<b>Length</b> 181±1.5 (7.13±0.06)		<p>Terminal Hardware Initial Torque: B1(2.5Nm±5%), I1(4.0Nm±5%)</p>
<b>Width</b> 76±1.5 (2.99±0.06)		
<b>Container Height</b> 166±1.5 (6.54±0.06)		
<b>Total Height</b> 166±1.5 (6.54±0.06)		

### Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell) \ Discharge Time	10 Min	15 Min	30 Min	40 Min	1 Hr	2 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	538.5	436.1	274.2	217.4	162.8	85.5	70.1	44.4	22.44	11.76
1.75V	583.5	456.8	285.1	225.4	167.5	87.8	71.5	44.9	22.80	12.00
1.70V	604.8	470.6	291.2	229.7	170.3	88.7	72.0	45.2	22.92	12.12
1.65V	619.3	481.6	295.5	233.0	172.6	89.6	72.5	45.6	23.04	12.24
1.60V	631.6	490.8	298.3	235.4	174.5	90.0	73.0	45.7	23.04	12.24
1.50V	643.9	500.9	301.1	237.7	176.3	90.5	73.4	45.7	23.04	12.24

### Constant current discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell) \ Discharge Time	10 Min	15 Min	30 Min	40 Min	1 Hr	2 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	47.4	37.9	23.2	18.4	13.68	7.13	5.84	3.70	1.87	0.98
1.75V	51.4	39.7	24.2	19.0	14.07	7.31	5.96	3.74	1.90	1.00
1.70V	53.2	40.9	24.7	19.4	14.31	7.39	6.00	3.77	1.91	1.01
1.65V	54.5	41.9	25.0	19.7	14.50	7.46	6.04	3.80	1.92	1.02
1.60V	55.6	42.7	25.3	19.9	14.66	7.50	6.08	3.81	1.92	1.02
1.50V	56.7	43.6	25.5	20.1	14.82	7.54	6.12	3.81	1.92	1.02

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.  
A/2 REV. Jul. 2013