



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





VRLA Rechargeable Battery

EB24-12



FEATURES

- Absorbent Glass Mat technology for efficient gas recombination
- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Can be used in any orientation(excluding used inverted)
- The battery is designed for high power & high cyclic usage
- Low self-discharge rate, lower than 3% capacity loss per month

APPLICATION

- UPS
- E-bike
- Wheelchairs
- Lawn Mowers
- Golf-Carts
- Electrical Scooter



SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	24Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	7350g(16.2lbs.)
Terminals	Type BE
Internal Resistance	≤10mΩ (Fully Charged)
Max. Discharge Current	360 A (5 sec.)
Max. Charge Current	7.2 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	Standard: ABS(UL 94-HB) EB24-12 Optional: Flame Retardant ABS(UL 94-V0) EB24-12FR

WSF ISO9001	UL MH19884
WSF ISO14001	CE CAM20310-2474-E-16
WSF OHSMS	
<ul style="list-style-type: none"> ● IEC 61056-1 ● JIS C 8702-1 ● GB/T 19639.1 	

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> ■ Length 183±1.5 (7.20±0.06) ■ Width 77±1.5 (3.03±0.06) ■ Container Height 170±1.5 (6.69±0.06) ■ Total Height 170±1.5 (6.69±0.06) 		<ul style="list-style-type: none"> ● Terminal BE

Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell) \ Discharge Time	10 Min	15 Min	30 Min	40 Min	1 Hr	2 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	646.2	523.3	329.1	260.9	195.36	114.0	84.1	53.2	26.93	14.11
1.75V	700.1	548.1	342.1	270.5	201.00	117.0	85.8	53.9	27.36	14.40
1.70V	725.8	564.7	349.4	275.6	204.36	118.2	86.4	54.3	27.50	14.54
1.65V	743.2	577.9	354.6	279.6	207.12	119.4	87.0	54.7	27.65	14.69
1.60V	757.9	589.0	358.0	282.4	209.40	120.0	87.6	54.9	27.65	14.69
1.50V	772.7	601.1	361.3	285.3	211.56	120.6	88.1	54.8	27.65	14.69

Constant current discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell) \ Discharge Time	10 Min	15 Min	30 Min	40 Min	1 Hr	2 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	56.9	45.5	27.9	22.0	16.42	9.50	7.01	4.44	2.24	1.18
1.75V	61.6	47.7	29.0	22.8	16.88	9.75	7.15	4.49	2.28	1.20
1.70V	63.9	49.1	29.6	23.3	17.17	9.85	7.20	4.52	2.29	1.21
1.65V	65.4	50.3	30.0	23.6	17.40	9.95	7.25	4.56	2.30	1.22
1.60V	66.7	51.2	30.3	23.9	17.59	10.00	7.30	4.57	2.30	1.22
1.50V	68.0	52.3	30.6	24.1	17.78	10.05	7.34	4.57	2.30	1.22

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.
A/2 REV. Jul. 2013