



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



EC210 Compact Conductivity/TDS Meter



Compact handheld Conductivity Meter with long life carbon rod combination electrode measures Conductivity, TDS and Temperature. Units of measure include $\mu\text{S}/\text{cm}$, mS/cm , ppm, °F, and °C. The meter features three ranges for Conductivity and TDS plus adjustable Temperature compensation factor to maintain accuracy.

Applications:

- Wastewater and drinking water analysis
- Environmental tests to determine the health of ponds, streams, wells, and other bodies of water
- Manufacturing processes such as component or PCB rinsing



Features

- Simultaneous display of Conductivity or TDS with Temperature
- Automatic Temperature Compensation
- Temperature compensation factor adjustable between 0 to 5.0% per °C
- Min/Max and Data Hold functions
- Auto Power Off with disable feature
- Use optional 1413 μS Conductivity Standard (EC-1413-P) for calibration
- Complete with Conductivity cell and 39" (1m) cable, 9V battery, and soft case

Specifications	Ranges	Max Resolution	Basic Accuracy
Conductivity	2000 $\mu\text{S}/\text{cm}$	1 $\mu\text{S}/\text{cm}$	$\pm 2\%$ FS
	20 mS/cm	0.01 mS/cm	
	100 mS/cm	0.1 mS/cm	
TDS	1200ppm	1ppm	$\pm 2\%$ FS
	12,000ppm	10ppm	
	66,000ppm	100ppm	
Temperature	32 to 122°F (0 to 50°C)	0.1°F/°C	$\pm 1.5^\circ\text{F}/0.8^\circ\text{C}$
Dimensions	Meter: 5.3 x 2.4 x 1.3" (135 x 60 x 33mm); Probe: 0.9" (22mm)D x 4.7" (120mm)L		
Weight	10.4oz (295g) includes probe and battery		

Ordering

EC210 Conductivity/TDS Meter
 EC-1413-P 1413 μS Conductivity Standard (2 bottles - 1 pint each)



UPC Code: 793950052105