

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







	2										1											
THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT COR														RP.								
				)A/ T		ANICE	TAD C175			JS in.[mm] T				TOOLS								
	PANDUIT PART #			WI	WIRE RAN AWG [ mm²]		TAB SIZE INCH [mm]	HOUSING COLOR	L± .03	W± .02	.02 H± .02 MAX WIRE INSULATION C		T - 100 CT - 460 CT - 550									
		EDNF 10-2	250F I	[ ∠	#12-1 1,0-6	10,01	.250 X .032 [6,3 X 0,8]	YELLOW	.95 [24,]]	.36 [9,1]	[ 6	27 3,9]	[ 5	.22 5,6]	C	Г-600 <sup>.</sup> Т-155 Т-250	1					
В										1											В	
NOTES:  1. UL LISTED AND CSA CERTIFIED FOR: A. STRANDED COPPER WIRE ONLY B. 600V MAX VOLTAGE RATING C. 257°F (125°C) MAX TEMP RATING  Termina												•	H		<u></u>							
	2. MATERIAL: A. STAMPING - BRASS, TIN PLATED B. SLEEVE - COPPER OR BRASS, TIN PLATED C. HOUSING - NYLON 6/6, COLOR IS TRANSLUCENT														<b>V</b>							
	3. WIRE STRIP LENGTH 9/32" +1/32 [7.1mm +0.8] — Funnel Wire																					
	5. SEE WWW.PANDUIT.COM FOR PACKAGE QUANTITIES  INDICATED BY PART NUMBER SUFFIX.  6. DIMENSIONS IN BRACKETS ARE METRIC EQUIVALENT																					
		0. UI	MEIN:	2 I OI,	ND 1	IN DH	(ACKETS ARE	E MEIRI	, EQUIVAL	_ENI				2	STED 20H3 8522		ERTIF LR312					
A	A F													STRONGHOLD FEMALE DISCONNECTS (250 SERIES) FULLY INSULATED NYLON, METAL SLEEVE #12-10 AWG  CUSTOMER DRAWING								
												ITEM REVISION NAME  00123SHG/00  DATASET FILE NAME						PANDU				
,													001238				MATERIAL:		UUI			
-			UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]  .x ± .1 [2.54] .xxx ± .005 [.127]  .xx ± .01 [.25] ANGLES ± 5°									SEE NOTES										
DA/20	00	2/18	JHNU	TMR	RGB	RELEAS	ED			00123SH		THIR			IRD ANG ROJECTIO	DANGLE ECTION S			H41672			
D10100DA/20	REV	DATE	BY	CHK	APR		DESC	RIPTION		ECN	JHNU		/18	CHK TMR	SCALE N7	TS.		SHT 1 0F	<b>I</b>	SIZE		
<b>.</b>	2														1							