

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

















DIMENSION

Dim L	Nx15.0
Dim B	(N-1)x15.0
Dim C	Nx15.0+19.0

N=Number of poles

Poles	Tolerance
2р~3р	±0.30
4p~5p	±0.50
6p~10p	±0.80

PART NO.: El xx C 1 x 3 10J0 G

10 10 poles

1

		- T	Τ
		V	7
•		Color	RoHS co
Solid block	0	Black (RAL9005)	(lead<4
No. of poles	2	Red (RAL3001/D)	In coppe
02 2 poles	3	Orange(RAL2011/P)	
03 3 poles	L	Yellow(RAI 1018/A)	

5 Green(RAL6018/T) 6 Blue (RAL5015/A) 8 Grey(RAL7035/D) 9 White(RAL1102)

C Green(RAL6018/U)

ompliant: +%) er Alloy

Dim L+30.0 Dim B 3.80 (3.1) (31.0) \Ø2.00 Dim C

3

RECOMMENDED P.C.B LAYOUT TOP VIEW

Material:

- ●ltem@Terminal housing:Thermoplastic (UL 94V-0)
- ●ltem⊕Clamp: Steel Stamping, Zinc plated
- ●ltem@Solder pin1 : Copper , Tin plated
- ●ltem @Solder pin2 : Copper , Tin plated
- ●ltem @Terminal screw: Zinc plating"-"slot type

IEC Electrical cULus ● Voltage rating: 600V 1000V

● Current rating: 125A 125A 35mm² Wire range:

● Solid wire(AWG): 2-20

Stranded wire(AWG): 2-20

● Torque(Lb-In): 36.5

• Screw: M5

● Wire strip length: 12–15mm

• Withstanding Voltage: 2.2KV

● Operating temperature: -40° C to +115° C

• Soldering temperature: 260° C±5° C/5 Sec

• Safety Approval: c us

-	mat'l. code			surface / tolerand					ce	projection			pro	duct	: fai	nily								
L							ASME Y14.5 V ASME Y14.					.5				TERMINAL BLOCK								
	ltr	ecn	no	dr	dat	е	tolera	nces (ınless	otherw	ise sp	pecified 1			title									
							angl	۵۱۶		X.±	0.5		_	ММ	_	TERMINAL BLOCK								
								⊆	<u>.</u>			(.X±0.3												
L							X*±	1		X.XX	±0.1		scale			RISING CLAMP,180D WIRE INLET,SOLID BLOCK								
L							dr	EVIN	ZHONG		041514					dwg no					sheet 1 of 1			size
L							engr	EVIN	1 ZH	ONG	041514		FCi		ElxxC1x310J0G Δ,									
L							chr	HAN	IKE F			041514 041514		' 🗐		EIXXCIX31030G							Α4	
							appd	Sł	1I JU							type CUSTOMER					Dra	wing		
	sheet		revi	sion	Α																			
	inde	ex	she	et	1																			

В

form: A4mmXLc

2

PDS: Rev :A 3

STATUS:Released

Printed: May 2842014

В