



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# EKI-25481

## 8Tx Managed Ethernet Switch with Wide Temperature



### Features

- All Fast Ethernet ports for 8 Copper (EKI-25481)
- Redundancy: Advantech X-Ring Pro, Dual Homing, Couple Ring, and RSTP/STP (802.1w/1d)
- Configuration: SNMP v1/v2c, Web
- Backplane (Switching Fabric): 1.6 Gbps
- Dual 12 ~ 48 V<sub>DC</sub> power input and 1 relay output
- Supports wide operating temperature -40 ~ 75°C
- DIP switch for configure port alarm and enable Ring master

### Introduction

EKI-25481 is a cost effective managed industrial Ethernet switch which supports Fast Ethernet. To enhance reliability in industrial communication network, it equipped with Advantech owned redundant network protocol -- X-Ring Pro, which provides users with an easy way to establish a redundant Ethernet network with ultra high-speed recovery time less than 20 ms. Furthermore, EKI-25481 also supports advanced network standards to optimize network performance, reduce maintenance cost, and secure network safety.

### Specifications

#### Communications

- **Standard** IEEE 802.3, 802.3u, 802.3x, 802.1d, 802.1w, 802.1p, 802.1Q
- **LAN** 10/100Base-TX
- **Transmission Distance** Ethernet : Up to 100 m
- **Transmission Speed** Up to 100 Mbps

#### Interface

- **Connectors** 8 x RJ45 ports
- **LED Indicators** System: PWR1, PWR2, P-Fail, R-Master  
Ethernet port: Link/Activity, Speed  
Fiber port: Link/Activity
- **Reset Button** Reset and restore to factory default

#### Network Management

- **Configuration** SNMP v1/v2c, Web
- **VLAN** IEEE 802.1Q, Port based VLAN
- **Redundancy** Advantech X-Ring Pro, Dual Homing, Couple Ring, IEEE 802.1d STP, and IEEE 802.1w RSTP
- **Security** IP access security
- **Traffic Control** IGMP Snooping/Query for multicast group management, rate limit and storm control
- **Diagnostics** Port Mirroring, SNTp, Syslog, SNMP Trap, Email Alert

#### Mechanism

- **Enclosure** IP30, metal shell with solid mounting kits
- **Dimensions (W x H x D)** 59.6 x 152 x 105 mm (2.35" x 5.98" x 4.13")
- **Mounting** DIN-rail, Wall

#### Power

- **Power Consumption** Max. 7.6 W
- **Power Input** 12 ~ 48 V<sub>DC</sub>, 24 V<sub>AC</sub> (18 ~ 30 V<sub>AC</sub>)
- **Fault Output** 1 Relay Output, 1A @ 24 V<sub>DC</sub>

#### Protection

- **Power Reverse** Present
- **Overload Current** Present

#### Environment


- **Operating Temperature** -40 ~ 75°C (-40 ~ 167°F)
- **Storage Temperature** -40 ~ 85°C (-40 ~ 185°F)
- **Operating Humidity** 5 ~ 95% (non-condensing)
- **Storage Humidity** 5 ~ 95% (non-condensing)
- **MTBF** 215,266 hours

#### Certification

- **Safety** UL 508  
Class 1, Division 2
- **EMI** FCC Part 15 Subpart B Class A, EN 55022 Class A
- **EMS** EN 61000-4-2  
EN 61000-4-3  
EN 61000-4-4  
EN 61000-4-5  
EN 61000-4-6  
EN 61000-4-8
- **Shock** IEC 60068-2-27
- **Freefall** IEC 60068-2-32
- **Vibration** IEC 60068-2-6

## Dimensions

Unit: [mm]



Panel Cut-out Dimensions: 114 x 152 x 59.6 mm (4.49" x 5.99" x 2.35")

## Ordering Information

- EKI-2548I 8Tx Managed Ethernet Switch w/Wide Temp