



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



EKI-7712G-4FP EKI-7712G-4FPI

8G+4SFP Port Gigabit Managed Redundant Industrial PoE Switch



Features

- 8 x IEEE 802.3 at/at PoE Gigabit ports + 4 SFP ports
- SFP socket for Easy and Flexible Fiber Expansion
- Redundancy: X-Ring Pro (ultra high-speed recovery time < 20 ms), RSTP/STP (802.1w/1D)
- IXM function enables fast deployment
- Security: 802.1x (Port-Based, MD5/TLS/TTLS/PEAP Encryption), RADIUS
- Management: SNMP v1/v2c/v3, WEB, Telnet, Standard MIB, Private MIB
- NEMA TS2 for Traffic Control
- EN50121-4 approval for Railway trackside deployment
- -40 ~ 75°C wide-range operating temperature (EKI-7712G-4FPI)
- Dual 48 V_{DC} power input and 1 relay output
- Support Security Pack to against internal and external cyber threats

Introduction

EKI-7712G-4FP/4FPI supports 8 Gigabit IEEE 802.3 at/at PoE ports and 4 SFP (mini-GBIC) ports. They can provide up to 30 watts per port to fulfill high power consumption PD (Power Device) requirements. They are embedded with Advantech's IXM function, which can benefit users for fast deployment and can dramatically save engineers time and cost. The EKI-7712G series also supports NMS to help IT managers with networking maintenance and failure prevention. Finally, the EKI-7712G series is equipped with X-Ring Pro which can achieve ultra high speed recovery time of less than 20 ms to ensure network stability. The switch also features a wide -40° to 75°C operating temperature (EKI-7712G-4FPI) and NEMA TS2 rating, making the switch an ideal solution for use in traffic applications. EKI-7712G-4FP/4FPI has successfully passed the EN50121-4 European railway standard requirements for emissions and railway platform and trackside deployment.

Specifications

Interface

- **I/O Port** 8 x 10/100/1000Base-T/TX RJ-45
4 x SFP (mini-GBIC) port
- **Console port** RS-232 (RJ45)
- **Power Connector** 6-pin screw Terminal Block (including relay)

Physical

- **Enclosure** Metal Shell
- **Protection Class** IP 30
- **Installation** DIN-Rail
- **Dimensions (W x H x D)** 74 x 152 x 105 mm (2.91" x 5.98" x 4.13")

LED Display

- **System LED** PWR1, PWR2, SYS, Alarm and R.M.
- **Port LED** Link / Speed / Activity

Environment

- **Operating Temperature** -40 ~ 75°C (-40 ~ 167°F) (7712G-4FPI)
-10 ~ 60°C (-40 ~ 140°F) (7712G-4FP)
- **Storage Temperature** -40 ~ 85°C
- **Ambient Relative Humidity** 10 ~ 95% (non-condensing)
- **Humidity** 10 ~ 95% (non-condensing)

Power

- **Power Consumption** 12.1W @ 48V_{DC} (System)
- **Power Input** 48 V_{DC} (46 to 57 V_{DC}),
53 ~57 V_{DC} is recommended for 802.3at,
redundant dual power input
- **Power Budget** 240W
- **Fault Output** 1 Relay Output

Certification


- **EMI** CE, FCC Class A
- **Safety** UL61010-2-201
IEC60950*
- **EMC** EN 61000-4-2
EN 61000-4-3
EN 61000-4-4
EN 61000-4-5
EN 61000-4-6
EN 61000-4-8
EN50121-4
- **Shock** IEC 60068-2-27
- **Freefall** IEC 60068-2-32
- **Vibration** IEC 60068-2-6
- **Traffic control** NEMA TS2
- *= Compliant
- **Patent** <http://www.advantech.com/legal/patent>

L2 Features

- **L2 MAC Address** 8K
- **Jumbo Frame** 9216 Bytes
- **VLAN Group** 256 (VLAN ID 1 ~ 4094)
- **VLAN Arrange** Port based VLAN, Q-in-Q (VLAN Stacking), GVRP
- **Port Mirroring** Per port, Multi-source port,
IGMP Snooping v1/v2/v3, MLD
Snooping, IGMP Immediate leave
- **IP Multicast**
- **Storm Control** Broadcast, Multicast, Unknown unicast
- **Redundancy** IEEE 802.1D-STP, IEEE 802.1s-MSTP, IEEE
802.1w-RSTP, X-Ring Pro, with ultra high-speed
recovery time less than 20ms

Dimensions

Unit: mm [inch]



Panel Cut-out Dimensions: 105 x 152 x 74 (4.134" x 5.98" x 2.913")

QoS

- **Priority Queue Scheduling** WRR (Weighted Round Robin), SP (Strict Scheduling Priority) Hybrid Priority
- **Class of Service** IEEE 802.1p Based CoS, IP TOS, DSCP based CoS
- **Rate Limiting** Ingress Rate Limit, Egress Rate Limit
- **Link Aggregation** IEEE 802.3ad Dynamic Port Trunking, Static Port Trunking

Security

- **Port Security** Static, Dynamic IP Source Guard, ARP Spoofing Prevention, Access Control List, DHCP Snooping,
- **Authentication** 802.1x (Port-Based, MD5/TLS/TTLS/PEAP Encryption), TACACS+

Management

- **DHCP** Client, Server, Option66/67/82
- **Access** SNMP v1/v2c/v3, WEB, Telnet, RMON, Standard MIB, Private MIB
- **Security access** SSH2.0, SSL
- **Software upgrade** TFTP, HTTP, Dual Image
- **NTP** SNTP client

Ordering Information

- **EKI-7712G-4FPI-AE** 8GE + 4SFP Port Managed PoE Ethernet Switch w/Wide Temp
- **EKI-7712G-4FP-AE** 8GE + 4SFP Port Managed PoE Ethernet Switch