



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# VRLA Rechargeable Battery

## EP65-12



### FEATURES

- Absorbent Glass Mat technology for efficient gas recombination
- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Can be used in any orientation(excluding used inverted)
- The battery is designed for heavy duty cyclic application
- Low self-discharge rate, lower than 3% capacity loss per month

### APPLICATION

- UPS
- Golf-Carts
- Lawn Mowers



### SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	65Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	22.8Kg(50.30lbs.)
Terminals	B5 (Fitting M6 bolt & nut) I2 is optional
Internal Resistance	≤6mΩ (Fully Charged )
Max. Discharge Current	650 A (5 sec.)
Max. Charge Current	19.5 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage : -20°C~40°C(-4°F~104°F)
Container Material	Standard: ABS( UL 94-HB) EP65-12 Optional: Flame Retardant ABS(UL 94-V0) EP65-12FR

<b>ISO9001</b>	<b>UL</b> MH19884
<b>ISO14001</b>	<b>CE</b> CAM20310-2474-E-16
<b>OHSMS</b>	

- IEC 61056-1
- JIS C 8702-1
- GB/T 19639.1

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> <li>■ <b>Length</b> 350±2.0 (13.78±0.08)</li> <li>■ <b>Width</b> 166±2.0 (6.54±0.08)</li> <li>■ <b>Container Height</b> 174±2.0 (6.85±0.08)</li> <li>■ <b>Total Height</b> 174±2.0 (6.85±0.08)</li> </ul>		<ul style="list-style-type: none"> <li>● Terminal B5  </li> <li>● Terminal I2  </li> </ul> <p>[M6 BOLT &amp; NUT]      [M6 BOLT]</p> <p>Terminal Hardware Initial Torque: B5/ I2(5.5 Nm ± 5%)</p>

### Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell) \ Discharge Time	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	1568	1298	808	455.0	192.0	132.4	73.90	39.00
1.75V	1700	1362	842	469.0	195.6	134.9	74.70	39.60
1.70V	1769	1408	862	478.0	198.3	136.0	75.20	39.90
1.65V	1833	1442	878	484.0	199.2	136.5	75.50	40.20
1.60V	1878	1465	886	488.0	200.2	136.5	76.00	40.50

### Constant current discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell) \ Discharge Time	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	141.7	113.8	68.4	40.70	16.39	11.25	6.26	3.30
1.75V	155.7	119.4	71.0	42.30	16.60	11.36	6.35	3.37
1.70V	162.2	123.2	72.7	43.10	16.72	11.53	6.40	3.38
1.65V	166.7	126.7	73.6	43.70	16.78	11.57	6.42	3.39
1.60V	169.2	129.1	74.5	44.20	16.98	11.63	6.42	3.41

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.