



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# VRLA Rechargeable Battery

## EP80-12



### FEATURES

- Absorbent Glass Mat technology for efficient gas recombination
- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Can be used in any orientation(excluding used inverted)
- The battery is designed for heavy duty cyclic application
- Flame-arrestor is installed to ensure safety
- Low self-discharge rate, lower than 3% capacity loss per month

### APPLICATION

- UPS
- EV
- Telecom
- Golf-Carts



### SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	80Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	31.2Kg(68.8lbs.)
Terminals	B3 (Fitting M6 bolt & nut) I2 is optional
Internal Resistance	≤5.0mΩ (Fully Charged )
Max. Discharge Current	800 A (5 sec.)
Max. Charge Current	24 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage : -20°C~40°C(-4°F~104°F)
Container Material	Standard: ABS( UL 94-HB) EP80-12 Optional: Flame Retardant ABS(UL 94-V0) EP80-12FR

- IEC 60896-21/22
- JIS C 8704-2
- GB/T 19638.2

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> <li>■ <b>Length</b> 329±2.0 (12.95±0.08)</li> <li>■ <b>Width</b> 172±2.0 (6.77±0.08)</li> <li>■ <b>Container Height</b> 215±2.0 (8.46±0.08)</li> <li>■ <b>Total Height</b> B3:238±2.0 (9.37±0.08) I2:218.5±2.0(8.60±0.08)</li> </ul>		<p>Terminal Hardware Initial Torque: B3,I2(5.5Nm±5%)</p>

### Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell) \ Discharge Time	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	1586	1015	553	233	161	89.8	47.0
1.75V	1661	1054	569	238	163	91.2	48.0
1.70V	1711	1078	579	240	165	91.7	48.2
1.65V	1751	1093	587	242	166	91.9	48.3
1.60V	1785	1104	593	243	166	91.9	48.3

### Constant current discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell) \ Discharge Time	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	143	89.8	46.5	19.4	13.4	7.49	3.91
1.75V	151	93.3	47.8	19.8	13.6	7.60	4.00
1.70V	156	95.4	48.7	20.0	13.7	7.64	4.02
1.65V	159	96.7	49.4	20.2	13.8	7.66	4.03
1.60V	162	97.7	49.8	20.3	13.8	7.66	4.03

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.