



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Established Reliability Inductors

Physical Parameters and Environmental Characteristics	ER1641			ER1840		ER1537		ER1025		
	MIL-PRF-39010/01	MIL-PRF-39010/02	MIL-PRF-39010/03	MIL-PRF-39010/04	MIL-PRF-39010/05	MIL-PRF-39010/06	MIL-PRF-39010/07	MIL-PRF-39010/08	MIL-PRF-39010/09	MIL-PRF-39010/10
Inductance Range, μH	0.10 to 0.82	0.91 to 12.0	15 to 1000	0.15 to 2.7	3.0 to 27.0	0.15 to 4.7	5.1 to 240.0	0.10 to 1.00	1.1 to 27.0	30 to 1000
Core Material	Phenolic	Iron	Ferrite	Phenolic	Iron	Phenolic	Iron	Phenolic	Iron	Ferrite
Sleeve	Iron	Iron	Ferrite	—	—	—	—	—	—	—
Length, Inches	0.410 ± 0.020	0.410 ± 0.020	0.410 ± 0.020	0.437 ± 0.01	0.437 ± 0.01	0.375 ± 0.010	0.375 ± 0.010	0.250 ± 0.010	0.250 ± 0.010	0.250 ± 0.010
Millimeters	10.41 ± 0.51	10.41 ± 0.51	10.41 ± 0.51	11.10 ± 0.25	11.10 ± 0.25	9.53 ± 0.25	9.53 ± 0.25	6.35 ± 0.25	6.35 ± 0.25	6.35 ± 0.25
Diameter, Inches	0.162 ± 0.010	0.162 ± 0.010	0.162 ± 0.010	0.187 ± 0.010	0.187 ± 0.010	0.156 ± 0.010	0.156 ± 0.010	0.095 ± 0.010	0.095 ± 0.010	0.095 ± 0.010
Millimeters	4.11 ± 0.25	4.11 ± 0.25	4.11 ± 0.25	4.75 ± 0.25	4.75 ± 0.25	3.96 ± 0.25	3.96 ± 0.25	2.41 ± 0.25	2.41 ± 0.25	2.41 ± 0.25
Lead Size — AWG #	#22 TCW	#22 TCW	#22 TCW	#22 TCW	#22 TCW	#22 TCW	#22 TCW	#24 TCW	#24 TCW	#24 TCW
Inches	0.025 ± 0.002	0.025 ± 0.002	0.025 ± 0.002	0.025 ± 0.002	0.025 ± 0.002	0.025 ± 0.002	0.025 ± 0.002	0.020 ± 0.0015	0.020 ± 0.0015	0.020 ± 0.0015
Millimeters	0.635 ± 0.051	0.635 ± 0.051	0.635 ± 0.051	0.635 ± 0.051	0.635 ± 0.051	0.635 ± 0.051	0.635 ± 0.051	0.51 ± 0.04	0.51 ± 0.04	0.51 ± 0.04
Lead Length, Inches	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188
Millimeters	36.53 ± 4.77	36.53 ± 4.77	36.53 ± 4.77	36.58 ± 3.05	36.58 ± 3.05	36.53 ± 4.77	36.53 ± 4.77	36.53 ± 4.77	36.53 ± 4.77	36.53 ± 4.77
Weight Max. (Grams)	0.85	1.0	1.0	0.95	0.95	0.9	0.9	0.3	0.3	0.3
Current Rating at 90°C, Max. Rise °C	15	15	15	35	15	35	15	35	15	15
Operating Temp. °C	-55 to +105	-55 to +105	-55 to +105	-55 to +125	-55 to +105	-55 to +125	-55 to +105	-55 to +125	-55 to +105	-55 to +105
Max. Power Dissipation at 90°C, Watts	0.11	0.11	0.11	0.385	0.385	0.312	0.134	0.21	0.09	0.073
Coupling	3% Max.	3% Max.	3% Max.	—	—	—	—	—	—	—
Body Color	Black	Black	Black	Tan	Tan	Tan	Tan	Tan	Tan	Tan

MARKING EXAMPLE & ORDERING INFORMATION

M	39010/08	B	1R0	K	S
Military designator	Document sheet number	Class	Inductance	Inductance Tolerance	Failure rate level

CLASS: Identifies the maximum operating temperature:
Class A = 105°C Max.
Class B = 125°C Max.

HOW TO ORDER:
The Military Part Number consists of the document number and an assigned dash number as shown in the example.

MIL-PRF-39010 Molded RF Coils with Sn10 high-temperature solder for internal connections.

Approved Through Failure Rate Level S

Note The complete Military dash numbers will include two additional letters, indicated in the tables on the following three pages by **. The first additional letter will indicate tolerance: J indicates $\pm 5\%$; K indicates $\pm 10\%$; L indicates $\pm 20\%$.

The second letter will indicate the failure rate (e.g., M, P, R, S).

Packaging Tape & reel

ER1025: 12" reel, 3500 pieces max.; 14" reel, 6000 pieces max.
ER1537 and ER1641: 12" reel, 2500 pieces max.; 14" reel, 4000 pieces max.
ER1840: 12" reel, 2500 pieces max.; 14" reel, 3000 pieces max. For additional packaging options, see technical section.

Made in the U.S.A.

CONTINUED ON NEXT PAGE

ER SERIES (continued)

RF Inductors

DELEVAN PART NUMBER
 DASH NUMBER
 MILITARY
 INDUCTANCE (µH)
 IND. TOLERANCE (%)
 TEST FREQUENCY (MHz)
 Q MINIMUM
 SRF MINIMUM (MHz)
 MAXIMUM (OHMS @ 25°C)
 DC RESISTANCE (OHMS @ 25°C)
 CURRENT (mA)
 RATED DC

DELEVAN PART NUMBER
 DASH NUMBER
 MILITARY
 INDUCTANCE (µH)
 IND. TOLERANCE (%)
 TEST FREQUENCY (MHz)
 Q MINIMUM
 SRF MINIMUM (MHz)
 MAXIMUM (OHMS @ 25°C)
 DC RESISTANCE (OHMS @ 25°C)
 CURRENT (mA)
 RATED DC

MIL-PRF-39010/01

ER1641-101**	AR10**	0.10	5,10	50	25.0	250	0.025	1,790
ER1641-111**	AR11**	0.11	5	50	25.0	250	0.034	1,530
ER1641-121**	AR12**	0.12	5,10	50	25.0	250	0.034	1,530
ER1641-131**	AR13**	0.13	5	50	25.0	250	0.037	1,470
ER1641-151**	AR15**	0.15	5,10	50	25.0	250	0.037	1,470
ER1641-161**	AR16**	0.16	5	50	25.0	250	0.047	1,300
ER1641-181**	AR18**	0.18	5,10	50	25.0	250	0.047	1,300
ER1641-201**	AR20**	0.20	5	49	25.0	250	0.067	1,100
ER1641-221**	AR22**	0.22	5,10	49	25.0	250	0.067	1,100
ER1641-241**	AR24**	0.24	5	47	25.0	250	0.110	853
ER1641-271**	AR27**	0.27	5,10	47	25.0	250	0.110	853
ER1641-301**	AR30**	0.30	5	46	25.0	250	0.130	780
ER1641-331**	AR33**	0.33	5,10	46	25.0	250	0.130	780
ER1641-361**	AR36**	0.36	5	44	25.0	250	0.180	670
ER1641-391**	AR39**	0.39	5,10	44	25.0	250	0.180	670
ER1641-431**	AR43**	0.43	5	44	25.0	235	0.250	565
ER1641-471**	AR47**	0.47	5,10	44	25.0	235	0.250	565
ER1641-511**	AR51**	0.51	5	43	25.0	210	0.330	490
ER1641-561**	AR56**	0.56	5,10	43	25.0	210	0.330	490
ER1641-621**	AR62**	0.62	5	42	25.0	190	0.450	420
ER1641-681**	AR68**	0.68	5,10	42	25.0	190	0.450	420
ER1641-751**	AR75**	0.75	5	40	25.0	180	0.590	370
ER1641-821**	AR82**	0.82	5,10	40	25.0	180	0.590	370

MIL-PRF-39010/02

ER1641-911**	AR91**	0.91	5	44	25.0	140	0.070	1,070
ER1641-102**	A1R0**	1.00	5,10	44	25.0	140	0.070	1,070
ER1641-112**	A1R1**	1.10	5	44	7.9	130	0.100	895
ER1641-122**	A1R2**	1.20	5,10	44	7.9	130	0.100	895
ER1641-132**	A1R3**	1.30	5	44	7.9	115	0.120	815
ER1641-152**	A1R5**	1.50	5,10	44	7.9	115	0.120	815
ER1641-162**	A1R6**	1.60	5	44	7.9	105	0.140	755
ER1641-182**	A1R8**	1.80	5,10	44	7.9	105	0.140	755
ER1641-202**	A2R0**	2.00	5	44	7.9	100	0.190	650
ER1641-222**	A2R2**	2.20	5,10	44	7.9	100	0.190	650
ER1641-242**	A2R4**	2.40	5	44	7.9	92	0.280	535
ER1641-272**	A2R7**	2.70	5,10	44	7.9	92	0.280	535
ER1641-302**	A3R0**	3.00	5	44	7.9	85	0.350	480
ER1641-332**	A3R3**	3.30	5,10	44	7.9	85	0.350	480
ER1641-362**	A3R6**	3.60	5	44	7.9	75	0.400	450
ER1641-392**	A3R9**	3.90	5,10	44	7.9	75	0.400	450
ER1641-432**	A4R3**	4.30	5	44	7.9	70	0.550	380
ER1641-472**	A4R7**	4.70	5,10	44	7.9	70	0.550	380
ER1641-512**	A5R1**	5.10	5	44	7.9	65	0.720	335
ER1641-562**	A5R6**	5.60	5,10	44	7.9	65	0.720	335
ER1641-622**	A6R2**	6.20	5	44	7.9	55	1.020	280
ER1641-682**	A6R8**	6.80	5,10	50	7.9	55	1.020	280
ER1641-752**	A7R5**	7.50	5	50	7.9	50	1.320	245
ER1641-822**	A8R2**	8.20	5,10	50	7.9	50	1.320	245
ER1641-912**	A9R1**	9.10	5	50	7.9	46	1.620	220
ER1641-103**	A100**	10.00	5,10	50	7.9	46	1.620	220
ER1641-113**	A110**	11.00	5	50	2.5	44	2.000	200
ER1641-123**	A120**	12.00	5,10	50	2.5	44	2.000	200

MIL-PRF-39010/03

ER1641-153**	A150**	15	5,10	45	2.50	49.0	0.80	315
ER1641-163**	A160**	16	5	45	2.50	45.0	0.89	300
ER1641-183**	A180**	18	5,10	45	2.50	45.0	0.89	300
ER1641-203**	A200**	20	5	45	2.50	41.0	0.96	290
ER1641-223**	A220**	22	5,10	45	2.50	41.0	0.96	290
ER1641-243**	A240**	24	5	45	2.50	38.0	1.19	260
ER1641-273**	A270**	27	5,10	45	2.50	38.0	1.19	260
ER1641-303**	A300**	30	5	45	2.50	34.0	1.37	240
ER1641-333**	A330**	33	5,10	45	2.50	34.0	1.37	240
ER1641-363**	A360**	36	5	45	2.50	29.0	1.93	205
ER1641-393**	A390**	39	5,10	50	2.50	29.0	1.93	205
ER1641-433**	A430**	43	5	50	2.50	27.0	2.11	195
ER1641-473**	A470**	47	5,10	50	2.50	27.0	2.11	195
ER1641-513**	A510**	51	5	50	2.50	25.0	2.23	190
ER1641-563**	A560**	56	5,10	50	2.50	25.0	2.23	190

MIL-PRF-39010/03 (continued)

ER1641-623**	A620**	62	5	50	2.50	21.0	2.44	180
ER1641-683**	A680**	68	5,10	50	2.50	21.0	2.44	180
ER1641-753**	A750**	75	5	50	2.50	10.5	2.70	170
ER1641-823**	A820**	82	5,10	50	2.50	10.5	2.70	170
ER1641-913**	A910**	91	5	50	2.50	10.0	3.12	160
ER1641-104**	A101**	100	5,10	50	2.50	10.0	3.12	160
ER1641-114**	A111**	110	5	50	0.79	9.7	3.60	150
ER1641-124**	A121**	120	5,10	55	0.79	9.7	3.60	150
ER1641-134**	A131**	130	5	55	0.79	8.5	4.10	140
ER1641-154**	A151**	150	5,10	55	0.79	8.5	4.10	140
ER1641-164**	A161**	160	5	55	0.79	8.0	4.40	135
ER1641-184**	A181**	180	5,10	55	0.79	8.0	4.40	135
ER1641-204**	A201**	200	5	55	0.79	7.5	5.00	125
ER1641-224**	A221**	220	5,10	55	0.79	7.5	5.00	125
ER1641-244**	A241**	240	5	55	0.79	7.0	5.80	115
ER1641-274**	A271**	270	5,10	55	0.79	7.0	5.80	115
ER1641-304**	A301**	300	5	55	0.79	6.5	6.40	110
ER1641-334**	A331**	330	5,10	55	0.79	6.5	6.40	110
ER1641-364**	A361**	360	5	55	0.79	6.2	7.40	105
ER1641-394**	A391**	390	5,10	60	0.79	6.2	7.40	105
ER1641-434**	A431**	430	5	60	0.79	5.7	9.50	92
ER1641-474**	A471**	470	5,10	60	0.79	5.7	9.50	92
ER1641-514**	A511**	510	5	60	0.79	4.7	10.50	90
ER1641-564**	A561**	560	5,10	60	0.79	4.7	10.50	90
ER1641-624**	A621**	620	5	60	0.79	4.5	11.80	80
ER1641-684**	A681**	680	5,10	60	0.79	4.5	11.80	80
ER1641-754**	A751**	750	5	60	0.79	4.2	13.00	80
ER1641-824**	A821**	820	5,10	60	0.79	4.2	13.00	80
ER1641-914**	A911**	910	5	60	0.79	3.8	17.50	70
ER1641-105**	A102**	1,000	5,10	60	0.79	3.8	17.50	70

MIL-PRF-39010/04

ER1840-00**	BR15**	0.15	5,10,20	55	25.0	510	0.030	2,900
ER1840-101**	BR16**	0.16	5	50	25.0	415	0.035	2,700
ER1840-01**	BR18**	0.18	5,10	50	25.0	415	0.035	2,700
ER1840-102**	BR20**	0.20	5	50	25.0	415	0.035	2,700
ER1840-02**	BR22**	0.22	5,10,20	50	25.0	415	0.035	2,700
ER1840-103**	BR24**	0.24	5	50	25.0	350	0.065	2,000
ER1840-03**	BR27**	0.27	5,10	50	25.0	350	0.065	2,000
ER1840-104**	BR30**	0.30	5	50	25.0	350	0.065	2,000
ER1840-04**	BR33**	0.33	5,10,20	50	25.0	350	0.065	2,000
ER1840-105**	BR36**	0.36	5	50	25.0	300	0.085	1,700
ER1840-05**	BR39**	0.39	5,10	50	25.0	300	0.085	1,700
ER1840-106**	BR43**	0.43	5	50	25.0	300	0.085	1,700
ER1840-06**	BR47**	0.47	5,10,20	50	25.0	300	0.085	1,700
ER1840-107**	BR51**	0.51	5	50	25.0	270	0.125	1,450
ER1840-07**	BR56**	0.56	5,10	50	25.0	270	0.125	1,450
ER1840-108**	BR62**	0.62	5	45	25.0	250	0.150	1,300
ER1840-08**	BR68**	0.68	5,10	45	25.0	250	0.150	1,300
ER1840-109**	BR75**	0.75	5	40	25.0	210	0.205	1,100
ER1840-09**	BR82**	0.82	5,10	40	25.0	210	0.205	1,100
ER1840-110**	BR91**	0.91	5	40	25.0	200	0.290	930
ER1840-10**	B1R0**	1.00	5,10	40	25.0	200	0.290	930
ER1840-111**	B1R1**	1.10	5	30	7.9	180	0.400	785
ER1840-11**	B1R2**	1.20	5,10	30	7.9	180	0.400	785
ER1840-112**	B1R3**	1.30	5	30	7.9	170	0.485	720
ER1840-12**	B1R5**	1.50	5,10	30	7.9	170	0.485	720
ER1840-113**	B1R6**	1.60	5	30	7.9	150	0.740	580
ER1840-13**	B1R8**	1.80	5,10	30	7.9	150	0.740	580
ER1840-114**	B2R0**	2.00	5	30	7.9	140	0.970	505
ER1840-14**	B2R2**	2.20	5,10	30	7.9	140	0.970	505
ER1840-15**	B2R4**	2.40	5	30	7.9	120	1.200	460
ER1840-16**	B2R7**	2.70	5,10	30	7.9	120	1.200	460

CONTINUED ON NEXT PAGE



ER SERIES (continued)

DELEVAN PART NUMBER
 DASH NUMBER
 MILITARY
 INDUCTANCE (µH)
 IND. TOLERANCE (%)
 TEST FREQUENCY (MHz)
 Q MINIMUM
 SRF MINIMUM (MHz)
 MAXIMUM (OHMS @ 25°C)
 DC RESISTANCE (OHMS @ 25°C)
 CURRENT (mA)
 RATED DC

DELEVAN PART NUMBER
 DASH NUMBER
 MILITARY
 INDUCTANCE (µH)
 IND. TOLERANCE (%)
 TEST FREQUENCY (MHz)
 Q MINIMUM
 SRF MINIMUM (MHz)
 MAXIMUM (OHMS @ 25°C)
 DC RESISTANCE (OHMS @ 25°C)
 CURRENT (mA)
 RATED DC

MIL-PRF-39010/05								
ER1840-17**	A3R0**	3.00	5	30	7.9	70	0.140	945
ER1840-18**	A3R3**	3.30	5,10	30	7.9	70	0.140	945
ER1840-19**	A3R6**	3.60	5	30	7.9	65	0.155	870
ER1840-20**	A3R9**	3.90	5,10	30	7.9	65	0.155	870
ER1840-21**	A4R3**	4.30	5	30	7.9	60	0.210	745
ER1840-22**	A4R7**	4.70	5,10	30	7.9	60	0.210	745
ER1840-23**	A5R1**	5.10	5	30	7.9	50	0.280	645
ER1840-24**	A5R6**	5.60	5,10	30	7.9	50	0.280	645
ER1840-25**	A6R2**	6.20	5	30	7.9	50	0.375	560
ER1840-26**	A6R8**	6.80	5,10	30	7.9	50	0.375	560
ER1840-27**	A7R5**	7.50	5	30	7.9	48	0.440	520
ER1840-28**	A8R2**	8.20	5,10	30	7.9	48	0.440	520
ER1840-29**	A9R1**	9.10	5	30	7.9	42	0.605	440
ER1840-30**	A100**	10.0	5,10	30	7.9	42	0.605	440
ER1840-31**	A110**	11.0	5	30	2.5	36	1.05	335
ER1840-32**	A120**	12.0	5,10	50	2.5	36	1.05	335
ER1840-33**	A130**	13.0	5	50	2.5	30	1.20	310
ER1840-34**	A150**	15.0	5,10	55	2.5	30	1.20	310
ER1840-135**	A160**	16.0	5	55	2.5	30	1.95	245
ER1840-35**	A180**	18.0	5,10	60	2.5	30	1.95	245
ER1840-136**	A200**	20.0	5	60	2.5	24	2.20	230
ER1840-36**	A220**	22.0	5,10	60	2.5	24	2.20	230
ER1840-37**	A240**	24.0	5	60	2.5	22	2.75	205
ER1840-38**	A270**	27.0	5,10	65	2.5	22	2.75	205

MIL-PRF-39010/06								
ER1537-00**	BR15**	0.15	5,10,20	50	25.0	525	0.030	2,450
ER1537-101**	BR16**	0.16	5	50	25.0	460	0.055	1,810
ER1537-01**	BR18**	0.18	5,10	50	25.0	460	0.055	1,810
ER1537-102**	BR20**	0.20	5	50	25.0	460	0.055	1,810
ER1537-02**	BR22**	0.22	5,10,20	50	25.0	460	0.055	1,810
ER1537-103**	BR24**	0.24	5	45	25.0	360	0.090	1,400
ER1537-03**	BR27**	0.27	5,10	45	25.0	360	0.090	1,400
ER1537-104**	BR30**	0.30	5	45	25.0	360	0.090	1,400
ER1537-04**	BR33**	0.33	5,10,20	45	25.0	360	0.090	1,400
ER1537-105**	BR36**	0.36	5	45	25.0	310	0.12	1,225
ER1537-05**	BR39**	0.39	5,10	45	25.0	310	0.12	1,225
ER1537-106**	BR43**	0.43	5	45	25.0	310	0.12	1,225
ER1537-06**	BR47**	0.47	5,10,20	45	25.0	310	0.12	1,225
ER1537-107**	BR51**	0.51	5	45	25.0	280	0.135	1,150
ER1537-07**	BR56**	0.56	5,10	50	25.0	280	0.135	1,150
ER1537-108**	BR62**	0.62	5	50	25.0	250	0.150	1,100
ER1537-08**	BR68**	0.68	5,10	50	25.0	250	0.150	1,100
ER1537-09**	BR75**	0.75	5	50	25.0	220	0.220	900
ER1537-10**	BR82**	0.82	5,10	50	25.0	220	0.220	900
ER1537-11**	BR91**	0.91	5	50	25.0	200	0.290	785
ER1537-12**	B1R0**	1.00	5,10	50	25.0	200	0.290	785
ER1537-13**	B1R1**	1.10	5	33	7.9	180	0.420	650
ER1537-14**	B1R2**	1.20	5,10	33	7.9	180	0.420	650
ER1537-15**	B1R3**	1.30	5	33	7.9	160	0.500	600
ER1537-16**	B1R5**	1.50	5,10	33	7.9	160	0.500	600
ER1537-17**	B1R6**	1.60	5	33	7.9	150	0.650	525
ER1537-18**	B1R8**	1.80	5,10	33	7.9	150	0.650	525
ER1537-19**	B2R0**	2.00	5	33	7.9	135	0.950	435
ER1537-20**	B2R2**	2.20	5,10	33	7.9	135	0.950	435
ER1537-21**	B2R4**	2.40	5	33	7.9	120	1.20	385
ER1537-22**	B2R7**	2.70	5,10	33	7.9	120	1.20	385
ER1537-23**	B3R0**	3.00	5	33	7.9	110	2.00	300
ER1537-24**	B3R3**	3.30	5,10	33	7.9	110	2.00	300
ER1537-25**	B3R6**	3.60	5	33	7.9	100	2.30	280
ER1537-26**	B3R9**	3.90	5,10	33	7.9	100	2.30	280
ER1537-27**	B4R3**	4.30	5	33	7.9	90	2.60	260
ER1537-28**	B4R7**	4.70	5,10	33	7.9	90	2.60	260

MIL-PRF-39010/07								
ER1537-29**	A5R1**	5.1	5	45	7.90	60.0	0.32	495
ER1537-30**	A5R6**	5.6	5,10	45	7.90	60.0	0.32	495
ER1537-31**	A6R2**	6.2	5	45	7.90	55.0	0.50	395
ER1537-32**	A6R8**	6.8	5,10	50	7.90	55.0	0.50	395
ER1537-33**	A7R5**	7.5	5	50	7.90	50.0	0.60	360
ER1537-34**	A8R2**	8.2	5,10	50	7.90	50.0	0.60	360
ER1537-35**	A9R1**	9.1	5	50	7.90	45.0	0.90	290
ER1537-36**	A100**	10.0	5,10	55	7.90	45.0	0.90	290
ER1537-37**	A110**	11.0	5	55	2.50	42.0	1.10	265
ER1537-38**	A120**	12.0	5,10	65	2.50	42.0	1.10	265
ER1537-39**	A130**	13.0	5	65	2.50	40.0	1.40	240
ER1537-40**	A150**	15.0	5,10	65	2.50	40.0	1.40	240
ER1537-41**	A160**	16.0	5	65	2.50	34.0	2.25	185
ER1537-42**	A180**	18.0	5,10	75	2.50	34.0	2.25	185
ER1537-43**	A200**	20.0	5	75	2.50	30.0	2.50	175
ER1537-44**	A220**	22.0	5,10	75	2.50	30.0	2.50	175
ER1537-46**	A240**	24.0	5	60	2.50	25.0	2.60	170
ER1537-48**	A270**	27.0	5,10	60	2.50	25.0	2.60	170
ER1537-50**	A300**	30.0	5	60	2.50	19.0	3.00	165
ER1537-52**	A330**	33.0	5,10	65	2.50	19.0	3.00	165
ER1537-54**	A360**	36.0	5	60	2.50	15.5	2.50	180
ER1537-56**	A390**	39.0	5	60	2.50	14.5	2.60	176
ER1537-58**	A430**	43.0	5	60	2.50	13.7	2.70	172
ER1537-60**	A470**	47.0	5	55	2.50	13.0	2.75	170
ER1537-62**	A510**	51.0	5	55	2.50	12.7	2.85	167
ER1537-64**	A560**	56.0	5	55	2.50	12.0	3.00	164
ER1537-66**	A620**	62.0	5	55	2.50	11.5	3.15	160
ER1537-68**	A680**	68.0	5	55	2.50	11.0	3.30	156
ER1537-70**	A750**	75.0	5	55	2.50	10.5	3.70	147
ER1537-72**	A820**	82.0	5	50	2.50	10.3	3.90	143
ER1537-74**	A910**	91.0	5	50	2.50	10.0	4.30	136
ER1537-76**	A101**	100.0	5	50	2.50	9.50	4.50	133
ER1537-78**	A111**	110.0	5	60	0.79	8.90	4.90	128
ER1537-80**	A121**	120.0	5	65	0.79	8.70	5.20	124
ER1537-82**	A131**	130.0	5	65	0.79	8.50	5.45	121
ER1537-84**	A151**	150.0	5	65	0.79	8.00	6.05	114
ER1537-86**	A161**	160.0	5	65	0.79	7.50	6.40	111
ER1537-88**	A181**	180.0	5	65	0.79	7.00	6.75	108
ER1537-90**	A201**	200.0	5	65	0.79	6.50	7.10	106
ER1537-92**	A221**	220.0	5	65	0.79	6.20	7.45	103
ER1537-94**	A241**	240.0	5	65	0.79	5.90	7.80	101

MIL-PRF-39010/08								
ER1025-94**	BR10**	0.10	5,10	40	25.0	680	0.08	1,350
ER1025-95**	BR11**	0.11	5	40	25.0	640	0.09	1,270
ER1025-96**	BR12**	0.12	5,10	40	25.0	640	0.09	1,270
ER1025-97**	BR13**	0.13	5	38	25.0	600	0.10	1,200
ER1025-00**	BR15**	0.15	5,10	38	25.0	600	0.10	1,200
ER1025-01**	BR16**	0.16	5	35	25.0	550	0.12	1,105
ER1025-02**	BR18**	0.18	5,10	35	25.0	550	0.12	1,105
ER1025-03**	BR20**	0.20	5	33	25.0	510	0.14	1,025
ER1025-04**	BR22**	0.22	5,10	33	25.0	510	0.14	1,025
ER1025-05**	BR24**	0.24	5	33	25.0	430	0.16	960
ER1025-06**	BR27**	0.27	5,10	33	25.0	430	0.16	960
ER1025-07**	BR30**	0.30	5	30	25.0	410	0.22	815
ER1025-08**	BR33**	0.33	5,10	30	25.0	410	0.22	815
ER1025-09**	BR36**	0.36	5	30	25.0	365	0.30	700
ER1025-10**	BR39**	0.39	5,10	30	25.0	365	0.30	700
ER1025-11**	BR43**	0.43	5	30	25.0	330	0.35	650
ER1025-12**	BR47**	0.47	5,10	30	25.0	330	0.35	650
ER1025-13**	BR51**	0.51	5	30	25.0	300	0.50	545
ER1025-14**	BR56**	0.56	5,10	30	25.0	300	0.50	545
ER1025-15**	BR62**	0.62	5	28	25.0	275	0.60	495
ER1025-16**	BR68**	0.68	5,10	28	25.0	275	0.60	495
ER1025-17**	BR75**	0.75	5	28	25.0	250	0.85	415
ER1025-18**	BR82**	0.82	5,10	28	25.0	250	0.85	415
ER1025-19**	BR91**	0.91	5	25	25.0	230	1.00	385
ER1025-20**	B1R0**	1.00	5,10	25	25.0	230	1.00	385

CONTINUED ON NEXT PAGE



ER SERIES (continued)

DELEVAN PART NUMBER
 DASH NUMBER
 MILITARY
 INDUCTANCE (µH)
 IND. TOLERANCE (%)
 Q MINIMUM
 TEST FREQUENCY (MHz)
 SRF MINIMUM (MHz)
 MAXIMUM (OHMS @ 25°C)
 DC RESISTANCE (OHMS @ 25°C)
 CURRENT (mA)
 RATED DC

DELEVAN PART NUMBER
 DASH NUMBER
 MILITARY
 INDUCTANCE (µH)
 IND. TOLERANCE (%)
 Q MINIMUM
 TEST FREQUENCY (MHz)
 SRF MINIMUM (MHz)
 MAXIMUM (OHMS @ 25°C)
 DC RESISTANCE (OHMS @ 25°C)
 CURRENT (mA)
 RATED DC

MIL-PRF-39010/09								
ER1025-21**	A1R1**	1.1	5	25	7.9	150	0.18	590
ER1025-22**	A1R2**	1.2	5,10	25	7.9	150	0.18	590
ER1025-23**	A1R3**	1.3	5	25	7.9	140	0.22	535
ER1025-24**	A1R5**	1.5	5,10	28	7.9	140	0.22	535
ER1025-25**	A1R6**	1.6	5	28	7.9	125	0.30	455
ER1025-26**	A1R8**	1.8	5,10	30	7.9	125	0.30	455
ER1025-27**	A2R0**	2.0	5	30	7.9	115	0.40	395
ER1025-28**	A2R2**	2.2	5,10	30	7.9	115	0.40	395
ER1025-29**	A2R4**	2.4	5	30	7.9	100	0.55	335
ER1025-30**	A2R7**	2.7	5,10	37	7.9	100	0.55	335
ER1025-31**	A3R0**	3.0	5	37	7.9	90	0.85	270
ER1025-32**	A3R3**	3.3	5,10	45	7.9	90	0.85	270
ER1025-33**	A3R6**	3.6	5	45	7.9	80	1.00	250
ER1025-34**	A3R9**	3.9	5,10	45	7.9	80	1.00	250
ER1025-35**	A4R3**	4.3	5	45	7.9	75	1.20	230
ER1025-36**	A4R7**	4.7	5,10	45	7.9	75	1.20	230
ER1025-37**	A5R1**	5.1	5	45	7.9	65	1.80	185
ER1025-38**	A5R6**	5.6	5,10	50	7.9	65	1.80	185
ER1025-39**	A6R2**	6.2	5	50	7.9	60	2.00	175
ER1025-40**	A6R8**	6.8	5,10	50	7.9	60	2.00	175
ER1025-41**	A7R5**	7.5	5	50	7.9	55	2.70	155
ER1025-42**	A8R2**	8.2	5,10	55	7.9	55	2.70	155
ER1025-43**	A9R1**	9.1	5	55	7.9	50	3.70	130
ER1025-44**	A100**	10.0	5,10	55	7.9	50	3.70	130
ER1025-45**	A110**	11.0	5	45	2.5	40	2.70	130
ER1025-46**	A120**	12.0	5,10	45	2.5	40	2.70	155
ER1025-47**	A130**	13.0	5	40	2.5	35	2.80	150
ER1025-48**	A150**	15.0	5,10	40	2.5	35	2.80	150
ER1025-49**	A160**	16.0	5	40	2.5	30	3.10	145
ER1025-50**	A180**	18.0	5,10	50	2.5	30	3.10	145
ER1025-51**	A200**	20.0	5	50	2.5	25	3.30	140
ER1025-52**	A220**	22.0	5,10	50	2.5	25	3.30	140
ER1025-53**	A240**	24.0	5	50	2.5	20	3.50	135
ER1025-54**	A270**	27.0	5,10	50	2.5	20	3.50	135

MIL-PRF-39010/10								
ER1025-55**	A300**	30.0	5	45	2.50	24	3.4	130
ER1025-56**	A330**	33.0	5,10	45	2.50	24	3.4	130
ER1025-57**	A360**	36.0	5	45	2.50	22	3.6	125
ER1025-58**	A390**	39.0	5,10	45	2.50	22	3.6	125
ER1025-59**	A430**	43.0	5	45	2.50	20	4.5	110
ER1025-60**	A470**	47.0	5,10	45	2.50	20	4.5	110
ER1025-61**	A510**	51.0	5	45	2.50	18	5.7	100
ER1025-62**	A560**	56.0	5,10	45	2.50	18	5.7	100
ER1025-63**	A620**	62.0	5	45	2.50	15	6.7	92
ER1025-64**	A680**	68.0	5,10	50	2.50	15	6.7	92
ER1025-65**	A750**	75.0	5	50	2.50	14	7.3	88
ER1025-66**	A820**	82.0	5,10	50	2.50	14	7.3	88
ER1025-67**	A910**	91.0	5	50	2.50	13	8.0	84
ER1025-68**	A101**	100	5,10	50	2.50	13	8.0	84
ER1025-69**	A111**	110	5	30	0.79	12	13.0	66
ER1025-70**	A121**	120	5,10	30	0.79	12	13.0	66
ER1025-71**	A131**	130	5	30	0.79	11	15.0	61
ER1025-72**	A151**	150	5,10	30	0.79	11	15.0	61
ER1025-73**	A161**	160	5	30	0.79	10	17.0	57
ER1025-74**	A181**	180	5,10	30	0.79	10	17.0	57
ER1025-75**	A201**	200	5	30	0.79	9.0	21.0	52
ER1025-76**	A221**	220	5,10	30	0.79	9.0	21.0	52
ER1025-77**	A241**	240	5	30	0.79	8.0	25.0	47
ER1025-78**	A271**	270	5,10	30	0.79	8.0	25.0	47
ER1025-79**	A301**	300	5	30	0.79	7.0	28.0	45
ER1025-80**	A331**	330	5,10	30	0.79	7.0	28.0	45
ER1025-81**	A361**	360	5	30	0.79	6.5	35.0	40
ER1025-82**	A391**	390	5,10	30	0.79	6.5	35.0	40
ER1025-83**	A431**	430	5	30	0.79	6.0	42.0	36
ER1025-84**	A471**	470	5,10	30	0.79	6.0	42.0	36
ER1025-85**	A511**	510	5	30	0.79	5.0	46.0	35
ER1025-86**	A561**	560	5,10	30	0.79	5.0	46.0	35
ER1025-87**	A621**	620	5	30	0.79	4.0	60.0	30
ER1025-88**	A681**	680	5,10	30	0.79	4.0	60.0	30
ER1025-89**	A751**	750	5	30	0.79	3.8	65.0	29
ER1025-90**	A821**	820	5,10	30	0.79	3.8	65.0	29
ER1025-91**	A911**	910	5	30	0.79	3.4	72.0	28
ER1025-92**	A102**	1,000	5,10	30	0.79	3.4	72.0	28

