## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Product specifications



## Core **ER35/21/11**



Effective parameters					
	Parameter	Value	Unit		
Σ(I/A)	core factor (C1)	0.849	mm⁻¹		
Ve	effective volume	9710	mm³		
Le	effective length	90.8	mm		
Ae	effective area	107	mm²		
Amin	minimum area	100	mm²		
m	ER35/21/11	≈ 23	g/pcs		

Dimensions for product: ER35/21/11						
	Nom	Tol +	Tol -	Max	Min	Unit
Α	35.00	0.65	0.65	35.65	34.35	mm
В	11.40	0.35	0.35	11.75	11.05	mm
D2	26.15	0.55	0.55	26.70	25.60	mm
D3	11.30	0.25	0.25	11.55	11.05	mm
E	20.70	0.20	0.20	20.90	20.50	mm
F	14.75	0.35	0.35	15.10	14.40	mm

Inductance factor						
Material	Value	Tol +	Tol -	Unit		
3C94	2800	25%	25%	nH/turns <sup>2</sup>		

Power loss: 3C94					
Measuring conditions			Max	Unit	
100 kHz	200 mT	100 °C	4.900	W/set	

Bsat					
Measuring conditions			Material	Min	Unit
25 kHz	250 A/m	100 °C	3C94	320	mT