

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China











### **SUMMARY**

#### # Wires

Fluidic

 Low
 0

 High
 0

 Coax
 1

Triax 0

 Quad
 0

 Fiber
 0

Series 00

Termination type Female solder

0

IP rating 50

 Cable Ø
 0.00 - 0.00 mm

 Matching parts
 FFA.00.250.CTAC29

Status

Alternative part



Image is for illustrative purpose only

#### **Download**

Request a quote

Catalog

# **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model ERA\*: Fixed receptacle, nut fixing

Keying Circular (can rotate)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing : 0 - 0 mm

Variant

### **Performance**

Configuration 0.25 : 1 Coax (50 Ohm)

Insulator T: PTFE Rated Current 4 Amps

### **Specifications**

Contact Type: Coaxial 50 Ohm (Solder)

Max. Matings: 5000

Contact Dia.: 0.7 mm (0.028in) Bucket Dia.: 0.6 mm (0.024in) Test voltage: 2.1 kV (rms) R (max): 6.1 mOhm Vtest: 2100 V (AC), 3000 V (DC)

Impedance: 50 Ohm VSWR: 1.09 + 0.11 \* f/GHz


### **Others**

Endurance (Shell): 5000 mating cycles

F ret (min): 100 N IP Rating: 50

## **DRAWINGS**

#### **Draws**







### **Dimensions**

	А	В	E	L	М	<b>S1</b>	<b>S</b> 3	e
mm.	8	10.3	5.5	15	1	6.3	9	M7x0.5
in.	0,31	0,41	0,22	0,59	0,04	0,25	0,35	

# **RECOMMENDED BY LEMO**

**Tools** 

None

Cables