



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



CHEMTRONICS

Technical Data Sheet

TDS # 1054

Arctic Blast™ Freeze Spray

PRODUCT DESCRIPTION

Arctic Blast™ Freeze Spray is specifically designed for locating thermal intermittent electrical components and cooling printed circuit boards. Utilizing an ultra-low global warming potential coolant, this product offers the best cooling possible with the lowest global warming impact. Arctic Blast™ Freeze Spray is nonflammable, residue-free and provides fast cooling action.

- Cools surfaces to below -49°F / -45 °C
- Ultra-low global warming impact of 6
- Nonflammable
- High heat transfer
- Pinpoint spray for individual component isolation
- Noncorrosive
- Ultra-pure, filtered to <0.2 microns
- Leaves no residue
- Nonabrasive on most surfaces
- CFC, HCFC and HFC free
- VOC free

TYPICAL APPLICATIONS


Arctic Blast™ Freeze Spray can be used to:

- Cool Equipment for Testing
- Dissipate Heat While Soldering or Desoldering
- Isolate Thermal Intermittent Components
- Test Circuit Traces for Continuity
- Test Printed Circuit Boards for Stress Fractures
- Track Intermittent Failures and Shorts

COMPATIBILITY

Arctic Blast™ Freeze Spray is generally compatible with most materials used in printed circuit board fabrication, including sensitive plastics and compounds. With any circuit refrigerant, compatibility must be determined on a non-critical area prior to use.

TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

Boiling Point	-2 °F / -19 °C
Cools To:	-49 °F / -45 °C
Vapor Density (air=1) @ 70°F	4.0
Solubility in Water @ 70°F / 1 atm	>0.10% by weight
Specific Gravity (water = 1 @ 70°F)	1.17
Evaporation Rate (butyl acetate=1)	>1
Appearance	Clear, Colorless Liquified Gas
Odor	Slight Ethereal
Internal Pressure	47 psia @ 70 °F
Flash Point (TCC)	None
Shelflife	5 years
RoHS/WEEE Status	

<u>Material</u>	<u>Compatibility</u>
Buna-N	Good
Graphite	Excellent
HDPE	Fair
LDPE	Fair
Lexan™	Good
Neoprene	Good
Cross-Linked PE	Good
Polyacrylate	Good
Polystyrene	Good
PVC	Good
Silicone Rubber	Fair
Teflon™	Fair
Viton™	Poor

USAGE INSTRUCTIONS

For industrial use only.
 Read MSDS carefully prior to use.
 No special surface preparation is required prior to using Arctic Blast™ Freeze Spray. Direct spray onto the area to instantly cool components, circuit boards or adhesives. For optimum performance and pin point control, use Arctic Blast™ Freeze Spray with the attached extension tube.

AVAILABILITY

ES1054 10 oz. Aerosol

DISTRIBUTED BY:

TECHNICAL & APPLICATION ASSISTANCE

Chemtronics provides a technical hotline to answer your technical and application related questions. The toll free number is: **1-800-TECH-401.**

ENVIRONMENTAL IMPACT DATA

ENVIRONMENTAL IMPACT DATA			
CFC	0.0%	VOC	0.0%
HCFC	0.0%	HFC	0.0%
CL Solv.	0.0%	ODP	0.0

CFC, HCFC, CL. SOLV., VOC, and HFC numbers shown are the content by weight. Ozone depletion potential (ODP) is determined in accordance with the Montreal Protocol and U.S. Clean Air Act of 1990. The ODP of this product is 0.0. It is the sum of the ODP of the substances that may contribute to the depletion of stratospheric ozone, based upon the weight of each substance in the product’s formulation. VOC consideration is based on the materials being not photochemically reactive by Commonly Used Standards (material supplier).

NOTE:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. CHEMTRONICS does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

Chemtronics® is a registered trademark of Chemtronics. All rights reserved. Arctic Blast™ is a trademark of Chemtronics. All rights reserved. All other trademarks herein are trademarks or registered trademarks of their respective owners.

CHEMTRONICS
 8125 COBB CENTER DRIVE
 KENNESAW, GA 30152
 1-770-424-4888

REV. B (08/13)