



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



CHEMTRONICS

Technical Data Sheet

TDS # 132

Flux-Off[®] Aqueous

PRODUCT DESCRIPTION

Flux-Off[®] Aqueous is an extra-strength water based cleaner for flux removal in ultrasonic, batch and in-line cleaning systems. It is an excellent cleaner for the removal of all rosin and no clean flux types from electronic subassemblies, printed circuit boards and all other electronic components. This concentrated formula can be diluted 1:10 with deionized water for handling all cleaning applications. Flux-Off[®] Aqueous will effectively remove other contaminants such as dirt, grease, handling soils and molding compounds.

- For use with ultrasonic, batch and in-line cleaning systems
- Quickly removes all rosin and no clean flux types
- Removes encrusted, hard, baked fluxes
- Powerful cleaner leaves no residue
- Contains no CFCs or HCFCs
- Nonabrasive and noncorrosive
- Nonflammable
- RoHS compliant

TYPICAL APPLICATIONS

Flux-Off[®] Aqueous removes flux residues and cleans:

- Chip Carriers
- Heat Sinks
- Metal Housings and Chassis
- Motors and Generators
- Printed Circuit Boards
- Surface Mount Device Pads

TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

Boiling Point	212°F (Initial)
Solubility in Water	100%
Specific Gravity	1.03
Flash Point (TCC)	None
Evaporation Rate (butyl acetate=1)	>1 (similar to water)
Appearance	Clear, Amber Liquid
Odor	Mild
Surface Tension (dynes/cm @ 73°F)	28.0
pH	12.5
VOC* Content:	
CARB and Federal rule 16 %	
SCAQMD Rule 1122 165 g/L concentrate	
17 g/L 1:10 dilution	
RoHS Compliant	
Shelflife	2 years after opening

*Volatile Organic Compound (VOC) information is calculated on a weight basis using the VOC definition of California Air Resources Board (CARB) Consumer Product Regulations, South Coast Air Quality Management District (SCAQMD) Rule 102 and the Federal definition published in 40 CFR 51.100(s).

COMPATIBILITY

Flux-Off[®] Aqueous is generally compatible with most materials used in printed circuit board fabrication. With any cleaning agent compatibility must be determined on a non-critical area prior to use.

<u>Material</u>	<u>Compatibility</u>
ABS Resin	Excellent
Buna-N	Fair
Butyl	Excellent
EPDM	Excellent
Graphite	Excellent
HDPE	Excellent
Kynar™	Excellent
LDPE	Excellent
Lexan™	Excellent
Neoprene	Good
Noryl®	Good
Nylon 101	Good
Cross-Linked PE	Good
Polyacrylate	Fair
Polypropylene	Good
Polystyrene	Good
PVC	Fair
Silicone Rubber	Good
Teflon™	Excellent
Viton™	Good

USAGE INSTRUCTIONS:

For industrial use only.

Read MSDS carefully prior to use.

Dilute 1:10 with deionized water for general cleaning. Can be used in hot or cold immersion, ultrasonic or aqueous cleaning systems. For immersion systems, soak as necessary. For ultrasonic cleaning, add Flux-Off® Aqueous to the ultrasonic cleaning tank, allow about two minutes for the mixture to degas, and immerse the part to be cleaned in the ultrasonic cleaner. After cleaning, rinse parts thoroughly in de-ionized water and dry where required.

AVAILABILITY

ES132 1 Gallon Liquid

ENVIRONMENTAL IMPACT DATA

HCFC-141b	None	HFC	None
HCFC-225	None	nPB	None

Hydrochlorofluorocarbons (HCFCs) are regulated under the Montreal Protocol as Class II ozone depleting substances. HCFC-141b is no longer produced in the US under this legislation. HCFC-225 is planned for production phase-out in 2015. Hydrofluorocarbons (HFCs) are not currently regulated.

EPA has listed n-propyl bromide (nPB) as an acceptable alternative to ozone depleting substances in metal, precision, and electronics cleaning under Section 612 of the Clean Air Act.

TECHNICAL & APPLICATION ASSISTANCE

Chemtronics provides a technical hotline to answer your technical and application related questions. The toll free number is: **1-800-TECH-401**.

NOTE:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly.

CHEMTRONICS does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

Chemtronics® and Flux-Off® are registered trademarks of Chemtronics. All rights reserved.

All other trademarks herein are trademarks or registered trademarks of their respective owners.

CHEMTRONICS

8125 COBB CENTER DRIVE

KENNESAW, GA 30152

1-770-424-4888

REV. F (08/13)

DISTRIBUTED BY: